

# FN1010 Load Pin



- Load Pin Design
- Range from 10 to 2000 kN (2 to 400 klbf)
- Other Ranges on Request
- Voltage or Current Output

## DESCRIPTION

Measurement Specialties, Inc.'s load pins, model **FN1010**, are designed to fit in the place of the regular mounting unit. The implantation is facilitated by the possibility of modifying a certain number of dimensions. The **FN1010** is suitable for numerous applications on lifting motors and handling equipment. The load pins can be used to measure forces on rotating components (pulleys, sheaves, etc.) and can be directly mounted on shackles.

The sensing element is fitted with thin film strain gauges in a Wheatstone bridge circuit. All **FN1010** Load Pins incorporate a keyed anti-rotation slot. Optionally, the load pins may be made watertight for certain applications while resting insensitive to hydrostatic pressure effects. Additionally, the **FN1010** is available with an integrated high-level analogue output.

With many years of experience as a designer and manufacturer of sensors, Measurement Specialties, Inc. often works with customers to design or customize sensors for specific uses and testing environments.

To meet your needs we also offer complete turnkey systems. The matched components (sensor, power, amplifier and digital display) are formatted, calibrated and ready for immediate use.

## FEATURES

- Full Scale Range : from 0-10 to 0-2000 kN (0-2 to 0-400 klbf)
- Tension and Compression
- Optional: Watertight
- High Coefficient of Security
- Optional: Watertight
- Bidirectional Versions Available
- Level Output Model with Integrated Amplifier

## APPLICATIONS

- Crane Monitoring
- Building Machine Monitoring
- Load-Limited Device
- Offshore

## STANDARD RANGES

Ranges in N	10k	20k	50k	100k	200k	500k	1 000k	2 000k
Ranges in lbf	2k	4k	10k	20k	40k	100k	200k	400k

# FN1010 Load Pin

## PERFORMANCE SPECIFICATIONS

All values are typical at temperature 20±1°C

PARAMETERS	
Operating Temperature Range (OTR)	-20 to 80° C [-4 to 176° F]
Compensated Temperature Range (CTR)	0 to 60° C [32 to 140° F]
Zero Shift in CTR	<0.5% F.S. / 50° C [/100° F]
Sensitivity Shift in CTR	<1% of reading / 50° C [/100° F]
Range (F.S.)	0-10 to 0-2000 kN [0-2 to 0-400 klbf]
Over-Range	
Without Damage	1.5 x F.S.
Without Destruction	5 x F.S.
Accuracy	
Combined Non-Linearity & Hysteresis	±1% F.S.

## Electrical Characteristics


Model	FN1010	FN1010-A1	FN1010-A2	FN1010-A3 (2 wires)
Supply Voltage	10Vdc	10–30Vdc	±15Vdc (±12 to ±18Vdc)	12-36Vdc
F.S. Output <sup>3</sup>	±1.5mV/V	±2V ±5% F.S.	±5V ±5% F.S.	4–20mA (4-12-20)
Zero Offset <sup>3</sup>	<±5% F.S.	2.5V ±5% F.S.	0V ±5% F.S.	4 (or 12mA)
Input Impedance/Consumption	350 to 700Ω	<50mA	<50mA	-
Output Impedance	350 to 700Ω	1 kΩ <sup>4</sup>	1 kΩ <sup>4</sup>	-
Insulation under 50Vdc	≥100MΩ	≥100MΩ	≥100MΩ	≥100MΩ

## Notes

1. Electrical Termination: Shielded cable; standard length 2m [6.5ft]
2. Materials: Body in stainless steel
3. Other output signal on request
4. Output impedance < 100 Ω on request
5. CE conformance according to EN 61010-1, EN 50081-1, EN 50082-1

# FN1010 Load Pin


## DIMENSIONS & WIRING SCHEMATIC (IN METRIC AND IMPERIAL)




All dimensions correspond to a standard. They can be modified, if necessary, for mounting. Please consult us for details.  
In order to simplify the use of load pins and limit the mechanical modifications associated with their implantation, all dimensions are given between two limits within which performances and characteristics can be maintained without increasing financial cost to the user.

**Note:** The delimiter groove can be placed on the output cable side.


### Wiring Schematic



### Version -A1



### Version -A2



### Dimensions in mm [inch]

F.S. Ranges in N [Lbf]		10k [2k]		20k [4k]		50k [10k]		100k [20k]		200k [40k]		500k [100k]		1000k [200k]		2000k [400k]	
A	Min.	22	[0.87]	27	[1.06]	30	[1.18]	42	[1.65]	54	[2.13]	82	[3.23]	110	[4.33]	150	[5.91]
	Nominal	25	[0.98]	30	[1.18]	35	[1.38]	45	[1.77]	60	[2.36]	90	[3.54]	120	[4.72]	160	[6.30]
	Max.	30	[1.18]	35	[1.38]	40	[1.57]	50	[1.97]	65	[2.56]	100	[3.94]	130	[5.12]	170	[6.69]
B	Min.	25	[0.98]	25	[0.98]	30	[1.18]	40	[1.57]	50	[1.97]	65	[2.56]	80	[3.15]	120	[4.72]
	Nominal	30	[1.18]	30	[1.18]	40	[1.57]	50	[1.97]	70	[2.76]	90	[3.54]	110	[4.33]	160	[6.30]
	Max.	35	[1.38]	35	[1.38]	50	[1.97]	65	[2.56]	90	[3.54]	115	[4.53]	140	[5.51]	200	[7.87]
C	Min.	10	[0.39]	10	[0.39]	15	[0.59]	20	[0.79]	25	[0.98]	30	[1.18]	40	[1.57]	60	[2.36]
	Nominal	15	[0.59]	15	[0.59]	20	[0.79]	25	[0.98]	30	[1.18]	40	[1.57]	55	[2.17]	80	[3.15]
	Max.	20	[0.79]	20	[0.79]	25	[0.98]	30	[1.18]	35	[1.38]	50	[1.97]	70	[2.76]	100	[3.94]
D	D	3	[0.12]	3	[0.12]	4	[0.16]	5	[0.20]	5	[0.20]	5	[0.20]	5	[0.20]	5	[0.20]
E	E	5	[0.20]	5	[0.20]	5	[0.20]	10	[0.39]	10	[0.39]	10	[0.39]	15	[0.59]	15	[0.59]

# FN1010 Load Pin

## OPTIONS

<b>A1</b> : Amplified Tension output with unipolar power supply
<b>A2</b> : Amplified Tension output with bipolar power supply
<b>A3</b> : Current output (2 wires)

## ORDERING INFO

<b>FN1010</b>	-	<b>A1</b>	-	<b>A00/B00/C00</b>	-	<b>100N</b>	-	<b>/SC</b>	
									Options (L00M, ..)
									Range in Newton
									Dimensions (see drawings)
									Amplified version (none, A1 or A2)
									Model

### NORTH AMERICA

Measurement Specialties, Inc.  
Vibration Design Center  
32 Journey - Suite 150  
Aliso Viejo, CA 92656  
United States USA  
Tel: 1-949-716-0877  
Fax: 1-949-916-5677  
[t&m@meas-spec.com](mailto:t&m@meas-spec.com)

### EUROPE

Measurement Specialties  
(Europe), Ltd.  
26 Rue des Dames  
78340 Les Clayes-Sous-Bois,  
France  
Tel: +33 (0) 130 79 33 00  
Fax: +33 (0) 134 81 03 59  
[cs.lcsb@meas-spec.com](mailto:cs.lcsb@meas-spec.com)

### ASIA

Measurement Specialties  
(China), Ltd.  
No. 26 Langshan Road  
Shenzhen High-Tech Park (North)  
Nanshan District, Shenzhen  
518057  
China  
Tel: +86 755 3330 5088  
Fax: +86 755 3330 5099  
[pfg.cs.asia@meas-spec.com](mailto:pfg.cs.asia@meas-spec.com)

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.