

Sales Information:

For Sales Inquires please email or contact us directly.

Sales Information : sales@estecom-usa.com

Technical Information : info@estecom-usa.com

Phone : (408) 496-6723

Fax : (408) 986-0309

GEOA190AU-PD03 19" monitors

BENEFITS :

- Designed to give state-of-the-art picture quality
- Analog RGB / DVI (Digital Video Interface)
- Full CRT multi-sync monitor compatibility
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- RS232 communication; remote control OSD function power on/off
- Application
 - Casino and amusement games
 - Information kiosks
 - Self-service
 - Industrial process control

SPECIFICATIONS

Model	GEOA190AU-PD03
Case	Galvanized sheet metal
Display Type	Size: 19.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 4 x 3
Useful screen area	Horizontal: 376.32 mm Vertical: 301.06 mm
Monitor dimensions	Width: 399.8 mm Height: 324 mm Depth: 38.1 mm
Optimal (native) resolution	1280 x 1024
Other supported resolutions	640 x 350 at 70Hz 640 x 400 at 70Hz 720 x 350 at 70Hz 720 x 400 at 70Hz 640 x 480 at 60~75Hz 800 x 600 at 60~75Hz 1024 x 768 at 60~75Hz 1152 x 864 at 60~75Hz 1280 x 960 at 60Hz 1280 x 1024 at 60~75Hz
Colors	16.7M
Brightness LCD panel	250 cd/m2 (typical)
Response time	5 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): 80° / 80° Vertical (up/down): 80° / 80°
Contrast ratio	1000:1 (typical)
Input video format	Analog RGB , DVI
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Input frequency	Horizontal: 31.5–80 kHz Vertical: 60–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12 VDC
Temperature	Operating: 0°C to 50°C Storage: 0°C to 50°C
Humidity	Operating: 5%–90% Storage: 5%–90% noncondensing
Weight (approx.)	Actual: TBD Shipping: TBD Shipping box dimensions: TBD
Touch interface	Option
Mounting options	Option

