

## GEIA150AU-PS08 15" Intelligent panel

### BENEFITS :

- Brilliant state-of-the-art LCD picture quality
- Analog RGB / DVI (Digital Video Interface)
- A full suite of touch screen options including: Resistive
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- RS232 communication; remote control OSD function power on/off
- Application
  - Kiosks
  - ATMs
  - Casino and amusement games
  - Lottery and ticket sales
  - Self-service
  - Industrial process control

### SPECIFICATIONS

Model	GEIA150AU-PS08
Case/bezel color	Galvanized sheet metal
Display Type	Size: 15.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 4 x 3
Useful screen area	Horizontal: 304.1 mm Vertical: 228.1 mm
Monitor dimensions	Width: 330.4 mm Height: 253.5 mm Depth: 21 mm
Optimal (native) resolution	1024 x 768
Other supported resolutions	640 x 350 at 70Hz 640 x 400 at 70Hz 720 x 350 at 70Hz 720 x 400 at 70Hz 640 x 480 at 60~75Hz 800 x 600 at 60~75Hz 1024 x 768 at 60~75Hz
Colors	16.2 million with dithering (8 bit)
Brightness LCD panel(w/o touch)	250 cd/m2 (typical)
Response time	8 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): 140° total Vertical (up/down): 125° total
Contrast ratio	700:1 (typical)
Input video format	Analog RGB and DVI
Input frequency	Horizontal: 31.5–80 kHz Vertical: 56–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12 VDC Current: 3A max.
Temperature	Operating: 0°C to 50°C Storage: -20°C to 50°C
Humidity	Operating: 8%–90% Storage: 8%–90%
Weight (approx.)	Packing: TBD Packing/5pcs: TBD Packing dimensions: TBD
Touch interface	None
Mounting options	



