

Sales Information:

For Sales Inquires please email or contact us directly.

Sales Information : sales@estecom-usa.com

Technical Information : info@estecom-usa.com

Phone : (408) 496-6723

Fax : (408) 986-0309

GEOA230SE-OD02 23" LED monitors

BENEFITS :

- Brilliant state-of-the-art LCD picture quality
- Analog RGB & DVI
- A full suite of touch screen options including: N/A
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- RS232 communication; remote control OSD function power on/off
- Application
 - Kiosks
 - ATMs
 - Casino and amusement games
 - Lottery and ticket sales
 - Self-service
 - Industrial process control

SPECIFICATIONS

Model	GEOA220SE-OD02
Case	Galvanized sheet metal
Display Type	Size: 23.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 16 x9
Useful screen area	Horizontal: 509.76 mm Vertical: 286.74 mm
Monitor dimensions	Width: 537 mm Height: 311.7 mm Depth: 50 mm
Optimal (native) resolution	1920 x 1080
Other supported resolutions	640 x 480 60~75Hz 800 x 600 60~75Hz 1024 x 768 60~75Hz 1152 x 864 60~75Hz 1280 x 1024 60~75Hz 1280 x 768 60~75Hz 1366 x 768 60~75Hz 1440 x 900 60~75Hz 1600 x1200 60~75Hz 1680 x1050 60Hz 1920 x 1080 60Hz 1920 x 1200 60Hz
Colors	16.7 millions
Brightness LCD panel	250 cd/m2 (typical)
Response time	5 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): 80° / 80° Vertical (up/down): 80° / 80°
Contrast ratio	1000:1 (typical)
Input video format	Analog RGB & DVI
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Input frequency	Horizontal: 31.5–80 kHz Vertical: 60–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12V DC
Temperature	Operating: 0°C to 50°C Storage: 0°C to 50°C
Humidity	Operating: 20%–90% Storage: 5%–90%
Weight (approx.)	Actual: TBD Shipping: TBD Shipping box dimensions: TBD
Touch interface	Option
Mounting options	4x side mounting Holes
Certification	None

