

Model

FPM-370LGFD01

Display Type	Size: 37.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 16 x 9
Monitor dimensions	Width: 877 mm Height: 517 mm Depth: 55.5 mm
Optimal (native) resolution	1920 x 1080
Other supported resolutions	640 x 480 60~75Hz 800 x 600 60~75Hz 1024 x 768 60~75Hz 1152 x 864 60~75Hz 1280 x 1024 60~75Hz 1280 x 768 60~75Hz 1366 x 768 60~75Hz 1440 x 900 60~75Hz 1600 x1200 60Hz 1680 x1050 60~75Hz 1920 x1080 60Hz
Colors	16.7 million with dithering(8 bit)
Response time	8 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): $\pm 89^\circ$ or 178° total Vertical (up/down): $\pm 89^\circ$ or 178° total
Contrast ratio	1200:1 (typical)
Input video format	Analog RGB & DVI
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 24V DC
Temperature	Operating: 0°C to 40°C Storage: -20°C to 60°C
Weight (approx.)	Actual(1pcs): 13 kg BOX(2pcs): 27 kg Shipping box dimensions: 895(L) X 350(W) X 590(H)
Touch interface	Option
Mounting options	Option

37" Widescreen

**THE WORLD IS WATCHING...****FOCAL POINT**