

GEOA121LG-LD01 12.1" LCD Mount monitors

BENEFITS :

- Designed to give state-of-the-art picture quality
- Analog RGB / DVI (Digital Video Interface)
- Full CRT multi-sync monitor compatibility
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- RS232 communication; remote control OSD function power on/off
- Application
 - Casino and amusement games
 - Information kiosks
 - Self-service
 - Industrial process control



SPECIFICATIONS

Model	GEOA121LG-LD01
Case	Steel
Display Type	Size: 12.1" diagonal Type: Active matrix TFT LCD
Useful screen area	Horizontal: 246 mm Vertical: 185 mm
Monitor dimensions	Width: 280 mm Height: 218mm Depth: 34mm
Optimal (native) resolution	800 x 600
Other supported resolutions	640 x 350 at 70Hz 640 x 400 at 70Hz 720 x 350 at 70Hz 720 x 400 at 70Hz 640 x 480 at 60~75Hz 800 x 600 at 60~75Hz
Colors	6-bit, 262,144 colors
Brightness	
LCD panel	300 cd/m2(Typ.)
Response time	55 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): ±60° or 120° total Vertical (up/down): ±60° or 120° total
Contrast ratio	200:1 (typical)
Input video format	Analog RGB , DVI & VIDEO
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Input frequency	Horizontal: 31.5–80 kHz Vertical: 60–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12 VDC
Temperature	Operating: 0°C to 40°C Storage: -20°C to 60°C
Humidity	Operating: 20%–80% Storage: 10%–90% noncondensing
Weight (approx.)	Actual: 1 kg Packing/10pcs: 12 kg Packing dimensions: TBD
Touch interface	Option
Mounting options	Option