



EIA170SE-L06 17" LCD Mount monitors

BENEFITS :

- Designed to give state-of-the-art picture quality
- Analog RGB / DVI (Digital Video Interface) / VIDEO
- Full CRT multi-sync monitor compatibility
- Single control operated & transparent On-Screen-Display (hereafter 'OSD') user interface
- RS232 communication; remote control OSD function power on/off

SPECIFICATIONS

Model	EIA170SE-L06
Case	Steel, AL(Optional)
Display Type	Size: 17.0" diagonal Type: Active matrix TFT LCD Aspect ratio: 5 x 4
Useful screen area	Horizontal: 338 mm Vertical: 270 mm
Monitor dimensions	Width: 357mm Height: 290 mm Depth: 20 mm
Optimal (native) resolution	1280 x 1024
Other supported resolutions	640 x 350 at 70Hz 640 x 400 at 70Hz 720 x 350 at 70Hz 720 x 400 at 70Hz 640 x 480 at 60~75Hz 800 x 600 at 60~75Hz 1024 x 768 at 60~75Hz 1152 x 864 at 60~75Hz 1280 x 960 at 60Hz 1280 x 1024 at 60~75Hz
Colors	16.7 million with dithering (8 bit)
Brightness LCD panel	250 cd/m2 (typical)
Response time	25 msec (typical)
Viewing angle (typical, from center)	Horizontal (left/right): ±89° or 178° total Vertical (up/down): ±89° or 178° total
Contrast ratio	600:1 (typical)
Input video format	Analog RGB , DVI & VIDEO
Input video signal connector	Mini D-Sub 15-Pin, DVI 24-Pin
Input frequency	Horizontal: 31.5–80 kHz Vertical: 60–75 Hz
Power supply	Type: External brick, 100–240 VAC, 50–60 Hz Monitor input voltage: 12 VDC
Temperature	Operating: 0°C to 40°C Storage: -20°C to 60°C
Humidity	Operating: 20%–80% Storage: 10%–90% noncondensing
Weight (approx.)	Actual: 2.7 kg Shipping: 16 kg Shipping box dimensions: 390(L) X 4320(W) X 470(H)
Touch interface	Option
Mounting options	Option



