



Tolerance on all dimensions: +/- 2mm unless stated otherwise

**Flex leads:**  
 Primary / HT: 16/0.2 TRI-rated  
 Secondary: 24/0.2mm and 32/0.2mm

**Core material:** grain orientated silicon steel  
**Transformer mass:** 2.77kg

**Chassis mounting frame**  
 or metal end shroud (shown) optional

**Electrical specification:**

Input voltage: 240V @ 50Hz  
 Magnetising current @ 240V: 135mA (typical)

Open circuit output voltages:

Secondary 1: 306 - 0 - 306 (regulation 5.2%)  
 Secondary 2: 6.8V (regulation 7.3%)  
 Secondary 3: 5.4V (regulation: 7.4%)

Hi-pot: 3.75kVAC for 2 seconds

**THIS TRANSFORMER MUST BE EARTHED**



**Walters Group Holdings Ltd.**  
 Unit 5, Oxonian Park, Langford Locks,  
 Kidlington, Oxfordshire. OX5 1FP  
 Tel: (01865) 855085 Fax: (01865) 855075  
 Website: www.oep.co.uk

DESCRIPTION	ISSUE	DATE	DRAWN	CHECKED	DRAWING NUMBER
172VA chassis mounting mains transformer with earth screen	1	13/03/12	CS		<b>W78580F</b>
	2	22/03/12	CS		
Scale: nts					
All dimensions in mm unless stated otherwise					