


## CF30 AC SERIES

MODEL No.	Hz	A	B	C	VOLTS	AMPS	W	RATED POWER RPM	SPEED mm/h2O	PRESSURE CFM	NOISE dBa	WEIGHT (G)
CF09830120BH	50/60	98	108	154	120	0.10/0.08	8/7	2700/3200	.8/1.1	10.8/14/4	30/32	390
CF09830230BH	50/60	98	108	154	230	0.06/0.04	8.5/7	2700/3200	.8/1.1	10.8/14/4	30/32	390
CF16030120BH	50/60	160	170	222	120	0.13/0.11	10/8.5	2700/3200	.9/1.2	21.6/28.8	32/35	520
CF16030230BH	50/60	160	170	222	230	0.07/0.06	10.5/9.5	2700/3200	.9/1.2	21.6/28.8	32/35	520
CF19830120BH	50/60	198	208	260	120	0.13/0.11	10/9	2700/3150	1.0/1.4	28.8/32.4	32/36	540
CF19830230BH	50/60	198	208	260	230	0.07/0.06	11/9.5	2700/3150	1.0/1.4	28.8/32.4	32/36	540
CF30030120BH	50/60	300	310	366	120	0.20/0.17	15/13.5	2700/3150	1.1/1.6	50.4/57.6	34/37	670
CF30030230BH	50/60	300	310	366	230	0.08/0.07	12.5/11.5	2700/3150	1.1/1.6	50.4/57.6	34/37	670



## CF40 AC SERIES

MODEL No.	Hz	A	B	C	VOLTS	AMPS	RATED POWER W	SPEED RPM	PRESSURE mm/h2O	CFM	NOISE dBa	WEIGHT (G)
CF09840120BH	50/60	98	108	160	120	0.13/0.11	10/9	2700/3150	1.8/2.5	28.8/36	36/38	520
CF09840230BH	50/60	98	108	160	230	0.07/0.06	11/9.5	2700/3150	1.8/2.5	28.8/36	36/38	520
CF16040120BH	50/60	160	170	222	120	0.14/0.12	11/10	2600/2800	1.9/2.7	43.2/50.4	36/38	570
CF16040230BH	50/60	160	170	222	230	0.07/0.06	11/10	2600/2800	1.9/2.7	43.2/50.4	36/38	570
CF19840120BH	50/60	198	208	260	120	0.14/0.12	12/11	2350/2350	2.0/2.8	50.4/50.4	36/35	590
CF19840230BH	50/60	198	208	260	230	0.07/0.06	12/11	2350/2350	2.0/2.8	50.4/50.4	36/35	590
CF30040120BH	50/60	300	310	366	120	0.21/0.20	17/16	2400/2200	2.1/2.9	86.4/75.6	38/36	720
CF30040230BH	50/60	300	310	366	230	0.09/0.08	14/13	2400/2200	2.1/2.9	86.4/75.6	38/36	720