



# 120x120x25mm

- **Airflow:** 61.2 CFM
- **Static Pressure:** 2.3 mm-H<sub>2</sub>O
- **Blade / Housing:** Plastic Material UL 94V-0 P.B.T.
- **Lead Wire:** UL1007 #24 AWG
- **Weight:** 118 g

DC AXIAL FAN

DC BLOWER

XTREME SERIES

AC AXIAL FAN

Model No.	Bearing	Rated Voltage	Operating Voltage Range	Speed	Max. Airflow	Max. Static Pressure	Current	Power Consumption	Life at 40°C L10	P-Q Curve	Noise Level
		VDC	VDC	RPM	CFM	mm-H <sub>2</sub> O	mA	W	Hour		dB(A)
KM12025012BL	2B	12	7~13.2	2000	61.2	2.3	180	2.16	80000	1	31.5
KM12025012BL(2)	2B		7~13.2	1200	38.4	1.4	70	0.84	80000	2	17.5
KM12025012LL	L		7~13.2	2000	61.2	2.3	65	0.78	50000	2	31.5
KM12025012LL(2)	L		7~13.2	1200	38.4	.78	70	0.78	50000	3	17.5
KM12025012SL	S		7~13.2	2000	61.2	2.3	180	2.16	30000	1	31.5
KM12025012SL(2)	S		7~13.2	1200	38.4	1.4	70	0.84	30000	2	17.5
KM12025012SL(1)	S		7~13.2	800	25.6	1.0	40	0.48	30000	3	16.5

**Buy Now**

2B: 2-ball bearing L: sintetico bearing S: sleeve bearing

Voltage Available

05 12 24 48


Bearing System Available

2B L S


Function Available

1 6 5 4 3 2 7 8 9 10 11 14 12 13

### PERFORMANCE P-Q CURVE



### OUTLINE DIMENSIONS



Please refer to *Model Numbering System* for bearing, function and speed level indication. Specifications are subject to changes without notice. Please refer to the formally issued product specification via contacting Y.S. TECH sales department. Visit Y.S. TECH web site at <http://www.ystechusa.com/> for updated information. Customized Specifications are designed accordingly.