


EFO Series

300-400 Watt 1U/High Density Power Supply



PRODUCT DESCRIPTION

The EF Series of switching power supplies utilizes advanced component and circuit technologies to deliver the industry's smallest 300-400 Watt switcher. Built to meet 1U height considerations, the U-Frame package measures only 6.80 x 3.86 x 1.40". All models offer universal AC input (85-265 VAC) with active power factor correction (PFC), optional 48 VDC input, flexible output configurations and compliance to worldwide safety and EMC standards. Features include:

- 300~400W compact high-density models
- Active load current share
- Universal AC input with PFC
- Ruggedized U-Channel construction
- 48V & 24V DC Input models available
- V2 option for 5~48 VDC
- RoHS compliant
- Includes OR-ing diode for N+1 parallel operation
- International regulatory approvals

INPUT

AC Input Voltage	90-264VAC, 47-63Hz
Input Inrush Current	< 30Amp@115VAC cold Start
Power Factor Correction	>0.98 Typical @ 110/220VAC input @ Full Load
Input Line Protection	6.3A 250VAC IEC Type
Hold-up Time	16mSec.@ Full Load

OUTPUT

Line Regulation	$\pm 0.1\%$ for V_{in} (min.) to V_{in} (max.)
Transient Response	Better than 5% For 50% Step Load
Over-Voltage Protection	120% Typical Latched Shut-down
Load Regulation	$\pm 1\%$ Max
Min. Load Requirement	None
Turn-On Delay	2 Sec. Max.
Initial Setting Accuracy	$\pm 1\%$
Ripple @ Noise	$\pm 1\%$ (20MHz bandwidth)
Overload Protection	125% Typical of Max Output Load

ENVIRONMENTAL

Operation Temperature	-5C to +50C. De-rate of 2.5% per 1Deg. C up to +71C
Temperature Protection	Shutdown (Internal Heat-Sink Temp. >90C), Auto recovery
Storage Temperature	-25C to +85C
Cooling	Forced Air Cooling 15CFM
Humidity	Up to 95% RH Non-condensing
Shock & Vibration	0.75G Peak 5Hz - 500Hz
MTBF	>300,000 Hours

STATUS & CONTROL

Remote Inhibit	ACTIVE Low-output shut down
DC Fail	Open Collector ACTIVE Low - Any Output drops below 10%
Current Share	Single Wire, $\pm 10\%$ accuracy
Remote Sense	Compensates for < 500mV drop
Auxiliary Output	5V / 5mA
V2 Option	5~48 VDC (Consult Factory)

ELECTROMAGNETIC COMPATIBILITY

Electrostatic Discharge	EN61000-4-2, ± 4 KV Contact / ± 8 KV Air Discharge
Radiated Susceptibility	EN61000-4-3, 26-1000MHz, 10V/M, 80% AM
EFT / Bursts	EN61000-4-4, ± 2 KV
Surges	EN61000-4-5, ± 2 KV Line-Earth, ± 1 KV Line-Line
Conducted Immunity	EN61000-4-6, 0.15-800MHz, 10V, 80% AM
Voltage Dips	EN61000-4-11, 95% Dip & 10ms, 30% Dip & 500ms
Voltage Interruptions	EN61000-4-11, 95% Reduction, 5s
Fluctuations & Flicker	EN61000-3-3

SAFETY & EMISSIONS

Safety Approvals	UL/cUL 60950-1
	VDE EN60950-1
	CE Marking



Digital Power
Flexible Power Solutions



EFO Series

300-400 Watt 1U/High Density Power Supply

Model Selection Guide





Model	Input	Output Power	Output Voltage	Output Current	Efficiency (Typical)
EFO306-105	90-264VAC	250 Watts	5V	50A	86%
EFO306-112	90-264VAC	350 Watts	12V	29A	86%
EFO306-115	90-264VAC	350 Watts	15V	23A	87%
EFO306-124	90-264VAC	350 Watts	24V	14.5A	87%
EFO306-128	90-264VAC	350 Watts	28V	12.5A	87%
EFO306-148	90-264VAC	350 Watts	48V	7.2A	88%
EFO306-154	90-264VAC	350 Watts	54V	6.4A	88%
EFO400-112	90-264VAC	400 Watts	12V	33A	86%
EFO400-124	90-264VAC	400 Watts	24V	16.6A	86%
EFO400-128	90-264VAC	400 Watts	28V	14.3A	86%
EFO400-148	90-264VAC	400 Watts	48V	8.3A	86%

Consult Digital power for DC input options, unique output voltages and other power levels.

J1 PINOUT	
1	GND
3	NEUTRAL
5	LINE

J2 PINOUT	
1	V2 RTN
2	V2

J3 PINOUT	
1	V1 ISHARE
2	V1 +RS
3	V1 -RS
4	DC FAIL
5	RETURN
6	+5V AUX
7	NONE
8	INHIBIT
9	NONE
10	NONE



NOTE :

MATING CONNECTOR FOR "J1"
CRIMP TERMINAL 08-52-0113 (x3)
HOUSING 09-50-3051 (x1)

MATING CONNECTOR FOR "J2"
CRIMP TERMINAL 08-52-0113 (x2)
HOUSING 09-50-3021 (x1)

MATING CONNECTOR FOR "J3"
CRIMP TERMINAL DF11-2428SC (x10)
HOUSING DF11-10DS-2C (x1)

INPUT J1

INPUT VOLT.	FREQUENCY	MAX. INPUT CURRENT	PHASE	PWR FACTOR COR.
90-250VAC	47-63Hz	4.5 AMPS	SINGLE	>0.9 @ P _o = 300W

Digital Power

NORTH AMERICA / ASIA
www.digipwr.com

Digital Power Corporation
41324 Christy Street
Fremont, CA 94538, USA

Phone (510) 657 2635
Fax (510) 657 6634
sales@digipwr.com

Revision A: 03/23/09 All specifications subject to change. Please consult Digital Power for latest specifications.

GRESHAM POWER
UK / EUROPE
www.greshampower.com

TELKOOR POWER
ISRAEL
www.telkoor.com

www.digipwr.com

Digital Power Corporation

Phone: (866) 344-7697