

Normally open type leaf switch LSA-1114 series

Features

- ◇ Superb reliability by adopting cross-bar contact.
- ◇ High quality by fully automated production process.
- ◇ Gold plated contact with high environment resistance is available.

Applications

- ◇ Mechanism for general audio and car audio products.
- ◇ For various kind of low current switching use.



Actual size

Zoom

Products Line , Typical Specifications


No	Products No.	No. of circuits	No. of contacts	Fixing method	Max rating (Resistive load)	Contact resistance (Initial performance / After lifetime)	Electrical life
1	LSA-1114H4AU	1	1	P.C.B. mounting	1 A 16 V DC	100 milliohm max. / 200 milliohm max.	20,000 cycles
2	LSA-1114L	1	1	P.C.B. mounting	1 A 16 V DC	100 milliohm max. / 200 milliohm max.	20,000 cycles
3	LSA-1114K3	1	1	P.C.B. mounting	1 A 16 V DC	100 milliohm max. / 200 milliohm max.	20,000 cycles

Dimensions

Unit : mm

No	Style	No	Style
1	<p>LSA-1114H4AU</p>	3	<p>LSA-1114K3</p>
2	<p>LSA-1114L</p>		

□ Circuit diagram

Circuit diagram

□ Notes

1. The appearance and specifications of the product may be modified without prior notice to improve its performance.
2. This catalog shows only outline specifications. When using the product, please obtain formal specifications.
3. Please see appendix [Cautions in Using Switches].
4. This switch is not washable.
5. Care shall be taken not to apply operating force more than specifications or the mechanical shock during operation of the switch.
6. In manual soldering, consideration should be given to apply the soldering iron to the tip of the terminal so that unusual pressure is not applied to the terminal.
7. Please do not apply pressure for 1 minute after soldering.
8. Care shall be taken not to attach flux on the terminal portion.