



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Tao-Yuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet for Product Specification

Issued Date:

Product Name: 376.6MHz IF SAW Filter (BW=75 MHz)

TST Parts No.: TB0378A

Customer Parts No.: _____

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Andy Yu

Approval by: _____ Francis Chen

Date: _____ 11/14/2006



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038

FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com

SAW Filter 376.6MHz (SMD 5.0×5.0 mm)

MODEL NO.: TB0378A

Rev. NO. 1

A. MAXIMUM RATINGS:

1. Input Power Level: 10 dBm
2. Operating Temperature: -20°C to 80°C
3. Storage Temperature: -40°C to 80°C

RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:

1. Ambient Temperature: 25 °C

Characteristics		Value			Note
		Min.	Typ.	Max.	
Center frequency F_c	MHz	-	376.6	-	-
Minimum Insertion loss I.L.	dB	-	15	16	-
1 dB Bandwidth	MHz	75	80	-	-
20 dB Bandwidth	MHz	-	94	115	-
Amplitude Ripple ($F_c \pm 37.5\text{MHz}$)	dB	-	0.85	1.0	-
Input Power	dBm	-	-	+10	-
Relative Rejection (Reference to Minimum Insertion loss)					
244.1~319.1 MHz	dBc	25	33	-	-
319.1~326.4 MHz	dBc	20	30	-	-

C. FREQUENCY CHARACTERISTICS:

(1) wide band of Response: (span: 300MHz)




Fig1.S21 Response Horizontal:30MHz/Div Vertical: 10dB/Div

(2) Passband of Response: (span: 100MHz)






Fig2.S21 Response Horizontal:10MHz/Div Vertical: 1dB/Div

D. TEST CIRCUIT:



$L1=30\text{nH}$, $C1=10\text{pF}$, $L2=27\text{nH}$, $C2=82\text{pF}$

E. OUTLINE DRAWING:




- Pin 1: RF input
- Pin 5: RF output
- Pin 4,8: Case Ground
- Pin 2,3,6,7: Ground
- : Week Code (Follow the table from planner each year)
- Unit : mm
- △ : Product / Year Code


Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>

F.PACKING:

1.REEL DIMENSION



2.TAPE DIMENSION



Direction of feed

G. Recommended Reflow Profile:

