



Material:

- Cable: UL20276 28AWG(7/0.12TC)*18+D(26AWGTC)+AL/MY+BRAID(85%)
O.D.: 7.5MM
- Connectors - P1&P2: DB 25P Male Soder Type Pin G/F Shell
NI-Plated (Insulator: Blue)
- Outer Jacket: 40P PVC
- Inner Jacket: Clear LD-PE
- Screw: #4-40UNC Type L=30MM, Nickel Plated
- Color: Beige

Electrical:

- 100% short, open, miswire test
- Contact resistance: 5Ω Max.
- Insulation resistance: 10MΩ Min.
- Hi-Pot: 300V DC / 10ms

Pin Assignment

P1	P2
1	1
18	18
2	2
19	19
3	3
19	19
4	4
20	20
5	5
20	20
6	6
21	21
7	7
21	21
8	8
22	22
9	9
22	22
10	10
24	24
11	11
23	23
12	12
24	24
13	13
24	24
14	14
25	25
16	16
25	25
15	15
23	23
17	17
25	25
SHELL	SHELL

Ⓜ = Assmann logo



ITEM NO.
AK737-3-R

TITLE IEEE 1284 Bi-Directional Connection Cable,
3 Meters, D-Sub 25 Pin Male <=>D-Sub 25 Pin Male

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED
©Copyright 2009 by Assmann Electronic Components
All International Rights Reserved