



P1

P2



1PCS / PE BAG

Material:

- Cable: Black USB1.1 UL2725 28#/1P+28#/2C+AEB
- OD: 3.8MM
- P1 Connector: USB Mini 5P Male
 - Pin: G/F
 - 3PCS Type
 - Insulator Color: Black
 - Shell: Nickel
 - Outer Jacket: Black PVC-40P
- P2 Connector: USB A Male
 - Pin: G/F
 - 4PCS Type
 - Insulator Color: White
 - Shell: Nickel
 - Outer Jacket: Black PVC-40

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 5Ω Max.
- Insulation Resistance: 10MΩ Min.
- Dielectric Test: 300V DC

Scale	1:1							Name
TOLERANCE						Drawn	08.29.11	Chappell
X.X	±0.40					Approved		
X.XX	±0.25							
X.XXX	±0.15							
Angle	±3°							
			Modification	Date	Name			

Item No.	Item Description	Unit	Quantity	Rate	Amount
----------	------------------	------	----------	------	--------

AK672M-5-R

Title	USB 1.1 Mini Cable, Mini 5P Male <=> A Male, 5.0 Meter
--------------	---

Drawing No.

rev00

Replace

Sheet

RoHS Complaint

ASSMANN
WVSW components