

Material:

- Cable: UL2725 [28AWG(7/0.127)*1PR+24AWG(7/0.203)*2C
  +AL-FOIL/MYLAR+DRAIN WIRE(7/0.127)+65% BRAID]TIN
  - OD: 4.7±0.15MM
  - PVC Jacket
  - Color: Black
- P1 Connector: USB A Type Male
  - Gold Plated 30μ" Contact
  - Nickel Plated Shell
- P2 Connector: USB A Type Female
  - Gold Plated 30μ" Contact
  - Nickel Plated Shell
- Hood: Molded Type, PVC 45P, Color Black
- Tooling Cavity indication for inspection

Electrical:

- 100% Open short & mis wire test
- Contact Resistance: 3Ω Max.
- Insulation Resistance: 20MΩ Min.

PIN OUT



RoHS Complaint

Scale	1:1						Name	Item No. AK669/2-18-BLACK-R
TOLERANCE					Drawn	08.29.11	Chappell	
X.X	±0.40				Approved	10.19.11	Warner	Title Hi-Speed USB 2.0 Extention cable, 1.8 Meters, Black, USB A Male <=> USB A Female
X.XX	±0.25							Drawing No. rev00
X.XXX	±0.15							
Angle	±3°							Replace Sheet
		Modification	Date	Name				

ASSMANN WSW components