

	1	2	3	4	5	6	7																																																															
A								A																																																														
B								B																																																														
C								C																																																														
D					Material: • Insulator: P.B.T. 30% Glass Fiber, UL 94V-0 • Contact Material: Phosphor Bronze, Gold flash over Nickel Electrical: • Current Rating: 1Amp • Insulation Resistance: 1,000MΩ Min. • Contact Resistance: 30MΩ Max. • Dielectric Withstanding: 500V AC • Operating Temperature: -40°C ~ +85°C			D																																																														
E								E																																																														
F								F																																																														
G	RoHS Complaint			<table><tr><td>Scale</td><td>1:1</td><td></td><td></td><td></td><td></td><td></td><td>Name</td><td>Item No.</td></tr><tr><td>TOLERANCE</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td rowspan="4">AWP60-7241-T-R</td></tr><tr><td>X.X</td><td>±0.40</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>10.19.11</td><td rowspan="3">Title IDC-Socket - 2.54MM Pitch, Gold Flash, Central Lug w/Strain Relief, 60 Contacts</td></tr><tr><td>X.XX</td><td>±0.25</td><td></td><td></td><td></td><td></td><td>Approved</td><td></td></tr><tr><td>X.XXX</td><td>±0.15</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>±3°</td><td></td><td></td><td></td><td></td><td></td><td></td><td>Drawing No.</td><td rowspan="2">rev00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>Replace</td><td>Sheet</td></tr></table>			Scale	1:1						Name	Item No.	TOLERANCE								AWP60-7241-T-R	X.X	±0.40					Drawn	10.19.11	Title IDC-Socket - 2.54MM Pitch, Gold Flash, Central Lug w/Strain Relief, 60 Contacts	X.XX	±0.25					Approved		X.XXX	±0.15							Angle	±3°							Drawing No.	rev00									Replace	Sheet	G
Scale	1:1						Name	Item No.																																																														
TOLERANCE								AWP60-7241-T-R																																																														
X.X	±0.40					Drawn	10.19.11		Title IDC-Socket - 2.54MM Pitch, Gold Flash, Central Lug w/Strain Relief, 60 Contacts																																																													
X.XX	±0.25					Approved																																																																
X.XXX	±0.15																																																																					
Angle	±3°							Drawing No.	rev00																																																													
								Replace		Sheet																																																												
H								H																																																														
	1	2	3	4	5	6	7																																																															