

	1	2	3	4	5	6	7																																																																																			
A									A																																																																																	
B									B																																																																																	
C	Conductor: [26AWG(0.16/7)Bare Copper]x6C Insulation: [PP6331 ID:0.95±0.03]x6C Jacket: PVC NOUL 65P								C																																																																																	
D	White Black Red Green Yellow Blue								D																																																																																	
E	6.8±0.2 2.4±0.2 SEC:△=△								E																																																																																	
F	120±10 140±10 A, B, C, D E, F, G								F																																																																																	
G	<table border="1"> <thead> <tr> <th>Part Number</th> <th>Drawing Number</th> <th>Wire Length "L"</th> <th>Jacket Color</th> <th>Cut Length</th> </tr> </thead> <tbody> <tr> <td>AT-S-26-6/6/W-5-R</td> <td>A</td> <td>1,525±20(5ft)</td> <td>White</td> <td>1,525-1,535mm</td> </tr> <tr> <td>AT-S-26-6/6/W-7-R</td> <td>B</td> <td>2,135±30(7ft)</td> <td>White</td> <td>2,135-2,145mm</td> </tr> <tr> <td>AT-S-26-6/6/W-10-R</td> <td>C</td> <td>3,050±60(10ft)</td> <td>White</td> <td>3,050-3,060mm</td> </tr> <tr> <td>AT-S-26-6/6/W-12-R</td> <td>D</td> <td>3,660±60(12ft)</td> <td>White</td> <td>3,660-3,670mm</td> </tr> <tr> <td>AT-S-26-6/6/W-14-R</td> <td>E</td> <td>4,270±60(14ft)</td> <td>White</td> <td>4,270-4,280mm</td> </tr> <tr> <td>AT-S-26-6/6/W-25-R</td> <td>F</td> <td>7,625±100(25ft)</td> <td>White</td> <td>7,625-7,635mm</td> </tr> <tr> <td>AT-S-26-6/6/W-50-R</td> <td>G</td> <td>15,250±150(50ft)</td> <td>White</td> <td>15,250-15,260mm</td> </tr> </tbody> </table>								Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-6/6/W-5-R	A	1,525±20(5ft)	White	1,525-1,535mm	AT-S-26-6/6/W-7-R	B	2,135±30(7ft)	White	2,135-2,145mm	AT-S-26-6/6/W-10-R	C	3,050±60(10ft)	White	3,050-3,060mm	AT-S-26-6/6/W-12-R	D	3,660±60(12ft)	White	3,660-3,670mm	AT-S-26-6/6/W-14-R	E	4,270±60(14ft)	White	4,270-4,280mm	AT-S-26-6/6/W-25-R	F	7,625±100(25ft)	White	7,625-7,635mm	AT-S-26-6/6/W-50-R	G	15,250±150(50ft)	White	15,250-15,260mm	G																																									
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																																																						
AT-S-26-6/6/W-5-R	A	1,525±20(5ft)	White	1,525-1,535mm																																																																																						
AT-S-26-6/6/W-7-R	B	2,135±30(7ft)	White	2,135-2,145mm																																																																																						
AT-S-26-6/6/W-10-R	C	3,050±60(10ft)	White	3,050-3,060mm																																																																																						
AT-S-26-6/6/W-12-R	D	3,660±60(12ft)	White	3,660-3,670mm																																																																																						
AT-S-26-6/6/W-14-R	E	4,270±60(14ft)	White	4,270-4,280mm																																																																																						
AT-S-26-6/6/W-25-R	F	7,625±100(25ft)	White	7,625-7,635mm																																																																																						
AT-S-26-6/6/W-50-R	G	15,250±150(50ft)	White	15,250-15,260mm																																																																																						
H	Unit: mm RoHS Compliant <table border="1"> <thead> <tr> <th>Scale</th> <th>Free</th> <th colspan="3"></th> <th>Date</th> <th>Name</th> <th colspan="2">Title</th> </tr> </thead> <tbody> <tr> <td colspan="2">TOLERANCE</td> <td colspan="3"></td> <td>Drawn</td> <td>08.07.13</td> <td>Wilson</td> <td>Modular cable - Straight</td> </tr> <tr> <td>X.</td> <td>±X</td> <td colspan="3"></td> <td>Approved</td> <td>08.07.13</td> <td>Groll</td> <td>6P6C 50µ", 26AWG, White, 5-50 feet</td> </tr> <tr> <td>X.X</td> <td>±X</td> <td colspan="3"></td> <td colspan="3"></td> <td>ASSMANN WSW-No.</td> </tr> <tr> <td>X.XX</td> <td>±X</td> <td colspan="3"></td> <td colspan="3"></td> <td>AT-S-26-6/6/W-xx-R</td> </tr> <tr> <td>DIM</td> <td>TOL</td> <td colspan="3"></td> <td colspan="3"></td> <td>Drawing-No.</td> </tr> <tr> <td>X.°</td> <td>±X°</td> <td colspan="3"></td> <td colspan="3"></td> <td>rev00</td> </tr> <tr> <td>X.X°</td> <td>±X°</td> <td colspan="3"></td> <td colspan="3"></td> <td>Replace</td> </tr> <tr> <td>Angle</td> <td>TOL</td> <td>Id.</td> <td>Modification</td> <td>Date</td> <td>Name</td> <td colspan="3">Sheet 1/1</td> </tr> </tbody> </table> ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us								Scale	Free				Date	Name	Title		TOLERANCE					Drawn	08.07.13	Wilson	Modular cable - Straight	X.	±X				Approved	08.07.13	Groll	6P6C 50µ", 26AWG, White, 5-50 feet	X.X	±X							ASSMANN WSW-No.	X.XX	±X							AT-S-26-6/6/W-xx-R	DIM	TOL							Drawing-No.	X.°	±X°							rev00	X.X°	±X°							Replace	Angle	TOL	Id.	Modification	Date	Name	Sheet 1/1			H
Scale	Free				Date	Name	Title																																																																																			
TOLERANCE					Drawn	08.07.13	Wilson	Modular cable - Straight																																																																																		
X.	±X				Approved	08.07.13	Groll	6P6C 50µ", 26AWG, White, 5-50 feet																																																																																		
X.X	±X							ASSMANN WSW-No.																																																																																		
X.XX	±X							AT-S-26-6/6/W-xx-R																																																																																		
DIM	TOL							Drawing-No.																																																																																		
X.°	±X°							rev00																																																																																		
X.X°	±X°							Replace																																																																																		
Angle	TOL	Id.	Modification	Date	Name	Sheet 1/1																																																																																				
	1	2	3	4	5	6	7																																																																																			