

	1	2	3	4	5	6	7																																																																																		
A								A																																																																																	
B								B																																																																																	
C								C																																																																																	
D	<table><tr><td>P1</td><td>P2</td></tr><tr><td>1 WHITE</td><td>8</td></tr><tr><td>2 ORANGE</td><td>7</td></tr><tr><td>3 BLACK</td><td>6</td></tr><tr><td>4 RED</td><td>5</td></tr><tr><td>5 GREEN</td><td>4</td></tr><tr><td>6 YELLOW</td><td>3</td></tr><tr><td>7 BLUE</td><td>2</td></tr><tr><td>8 BROWN</td><td>1</td></tr></table> A, B, C, D, F, G Note: - Material: Housing-polycarbonate, clear - Terminal-0.36[.014] thick phosphor bronze. Thick gold in localized gold plate. - Area, Gold Flash over the remainder. - Over 2.54mm[.000100] thick nickel underplate.							P1	P2	1 WHITE	8	2 ORANGE	7	3 BLACK	6	4 RED	5	5 GREEN	4	6 YELLOW	3	7 BLUE	2	8 BROWN	1	D																																																															
P1	P2																																																																																								
1 WHITE	8																																																																																								
2 ORANGE	7																																																																																								
3 BLACK	6																																																																																								
4 RED	5																																																																																								
5 GREEN	4																																																																																								
6 YELLOW	3																																																																																								
7 BLUE	2																																																																																								
8 BROWN	1																																																																																								
E	<table><thead><tr><th>Part Number</th><th>Drawing Number</th><th>Wire Length "L"</th><th>Jacket Color</th><th>Cut Length</th></tr></thead><tbody><tr><td>AT-S-26-8/8/B-5-R</td><td>A</td><td>1,525±20(5ft)</td><td>Black</td><td>1,525-1,535mm</td></tr><tr><td>AT-S-26-8/8/B-7-R</td><td>B</td><td>2,135±30(7ft)</td><td>Black</td><td>2,135-2,145mm</td></tr><tr><td>AT-S-26-8/8/B-10-R</td><td>C</td><td>3,050±60(10ft)</td><td>Black</td><td>3,050-3,060mm</td></tr><tr><td>AT-S-26-8/8/B-12-R</td><td>D</td><td>3,660±60(12ft)</td><td>Black</td><td>3,660-3,670mm</td></tr><tr><td>AT-S-26-8/8/B-14-R</td><td>E</td><td>4,270±60(14ft)</td><td>Black</td><td>4,270-4,280mm</td></tr><tr><td>AT-S-26-8/8/B-25-R</td><td>F</td><td>7,625±100(25ft)</td><td>Black</td><td>7,625-7,635mm</td></tr><tr><td>AT-S-26-8/8/B-50-R</td><td>G</td><td>15,250±150(50ft)</td><td>Black</td><td>15,250-15,260mm</td></tr></tbody></table>							Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-8/8/B-5-R	A	1,525±20(5ft)	Black	1,525-1,535mm	AT-S-26-8/8/B-7-R	B	2,135±30(7ft)	Black	2,135-2,145mm	AT-S-26-8/8/B-10-R	C	3,050±60(10ft)	Black	3,050-3,060mm	AT-S-26-8/8/B-12-R	D	3,660±60(12ft)	Black	3,660-3,670mm	AT-S-26-8/8/B-14-R	E	4,270±60(14ft)	Black	4,270-4,280mm	AT-S-26-8/8/B-25-R	F	7,625±100(25ft)	Black	7,625-7,635mm	AT-S-26-8/8/B-50-R	G	15,250±150(50ft)	Black	15,250-15,260mm	E																																									
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																																																					
AT-S-26-8/8/B-5-R	A	1,525±20(5ft)	Black	1,525-1,535mm																																																																																					
AT-S-26-8/8/B-7-R	B	2,135±30(7ft)	Black	2,135-2,145mm																																																																																					
AT-S-26-8/8/B-10-R	C	3,050±60(10ft)	Black	3,050-3,060mm																																																																																					
AT-S-26-8/8/B-12-R	D	3,660±60(12ft)	Black	3,660-3,670mm																																																																																					
AT-S-26-8/8/B-14-R	E	4,270±60(14ft)	Black	4,270-4,280mm																																																																																					
AT-S-26-8/8/B-25-R	F	7,625±100(25ft)	Black	7,625-7,635mm																																																																																					
AT-S-26-8/8/B-50-R	G	15,250±150(50ft)	Black	15,250-15,260mm																																																																																					
F								F																																																																																	
G	<table><tr><td>Scale</td><td>Free</td><td></td><td></td><td></td><td></td><td>Date</td><td>Name</td><td>Title</td></tr><tr><td colspan="2">TOLERANCE</td><td></td><td></td><td></td><td></td><td>Drawn</td><td>08.07.13</td><td>Wilson</td></tr><tr><td>X.</td><td>±X</td><td></td><td></td><td></td><td></td><td>Approved</td><td>08.07.13</td><td>Groll</td></tr><tr><td>X.X</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.XX</td><td>±X</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>DIM</td><td>TOL</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>X.X°</td><td>±X°</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Angle</td><td>TOL</td><td>Id.</td><td>Modification</td><td>Date</td><td>Name</td><td colspan="3">Replace</td></tr></table> Unit: mm RoHS Compliant ASSMANN WSW components 1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283 Toll Free: 1-877-277-6266 • Email: info@assmann.us							Scale	Free					Date	Name	Title	TOLERANCE						Drawn	08.07.13	Wilson	X.	±X					Approved	08.07.13	Groll	X.X	±X								X.XX	±X								DIM	TOL								X.°	±X°								X.X°	±X°								Angle	TOL	Id.	Modification	Date	Name	Replace			G
Scale	Free					Date	Name	Title																																																																																	
TOLERANCE						Drawn	08.07.13	Wilson																																																																																	
X.	±X					Approved	08.07.13	Groll																																																																																	
X.X	±X																																																																																								
X.XX	±X																																																																																								
DIM	TOL																																																																																								
X.°	±X°																																																																																								
X.X°	±X°																																																																																								
Angle	TOL	Id.	Modification	Date	Name	Replace																																																																																			
H	<table><tr><td colspan="2">Drawing-No.</td><td>rev00</td></tr><tr><td colspan="2">Sheet</td><td>1/1</td></tr></table>							Drawing-No.		rev00	Sheet		1/1	H																																																																											
Drawing-No.		rev00																																																																																							
Sheet		1/1																																																																																							
	1	2	3	4	5	6	7																																																																																		