

	1	2	3	4	5	6	7																																																										
A								A																																																									
B								B																																																									
C								C																																																									
D	<table><tr><td>P1</td><td>P2</td></tr><tr><td>1 WHITE</td><td>1</td></tr><tr><td>2 ORANGE</td><td>2</td></tr><tr><td>3 BLACK</td><td>3</td></tr><tr><td>4 RED</td><td>4</td></tr><tr><td>5 GREEN</td><td>5</td></tr><tr><td>6 YELLOW</td><td>6</td></tr><tr><td>7 BLUE</td><td>7</td></tr><tr><td>8 BROWN</td><td>8</td></tr></table> A, B, C, D E, F, G Note for plug: - Material: Housing-polycarbonate, clear. - Terminal-0.36[.014] thick phosphor bronze. - Thick gold in localized gold plate. - Area, Gold Flash over the remainder. - Over 2.54mm[.000100] thick nickel underplate. <table><thead><tr><th>Part Number</th><th>Drawing Number</th><th>Wire Length "L"</th><th>Jacket Color</th><th>Cut Length</th></tr></thead><tbody><tr><td>AT-S-26-8/8/B-5/R-R</td><td>A</td><td>1,525±20(5ft)</td><td>Black</td><td>1,525-1,535mm</td></tr><tr><td>AT-S-26-8/8/B-7/R-R</td><td>B</td><td>2,135±30(7ft)</td><td>Black</td><td>2,135-2,145mm</td></tr><tr><td>AT-S-26-8/8/B-10/R-R</td><td>C</td><td>3,050±60(10ft)</td><td>Black</td><td>3,050-3,060mm</td></tr><tr><td>AT-S-26-8/8/B-12/R-R</td><td>D</td><td>3,660±60(12ft)</td><td>Black</td><td>3,660-3,670mm</td></tr><tr><td>AT-S-26-8/8/B-14/R-R</td><td>E</td><td>4,270±60(14ft)</td><td>Black</td><td>4,270-4,280mm</td></tr><tr><td>AT-S-26-8/8/B-25/R-R</td><td>F</td><td>7,625±100(25ft)</td><td>Black</td><td>7,625-7,635mm</td></tr><tr><td>AT-S-26-8/8/B-50/R-R</td><td>G</td><td>15,250±150(50ft)</td><td>Black</td><td>15,250-15,260mm</td></tr></tbody></table>							P1	P2	1 WHITE	1	2 ORANGE	2	3 BLACK	3	4 RED	4	5 GREEN	5	6 YELLOW	6	7 BLUE	7	8 BROWN	8	Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length	AT-S-26-8/8/B-5/R-R	A	1,525±20(5ft)	Black	1,525-1,535mm	AT-S-26-8/8/B-7/R-R	B	2,135±30(7ft)	Black	2,135-2,145mm	AT-S-26-8/8/B-10/R-R	C	3,050±60(10ft)	Black	3,050-3,060mm	AT-S-26-8/8/B-12/R-R	D	3,660±60(12ft)	Black	3,660-3,670mm	AT-S-26-8/8/B-14/R-R	E	4,270±60(14ft)	Black	4,270-4,280mm	AT-S-26-8/8/B-25/R-R	F	7,625±100(25ft)	Black	7,625-7,635mm	AT-S-26-8/8/B-50/R-R	G	15,250±150(50ft)	Black	15,250-15,260mm
P1	P2																																																																
1 WHITE	1																																																																
2 ORANGE	2																																																																
3 BLACK	3																																																																
4 RED	4																																																																
5 GREEN	5																																																																
6 YELLOW	6																																																																
7 BLUE	7																																																																
8 BROWN	8																																																																
Part Number	Drawing Number	Wire Length "L"	Jacket Color	Cut Length																																																													
AT-S-26-8/8/B-5/R-R	A	1,525±20(5ft)	Black	1,525-1,535mm																																																													
AT-S-26-8/8/B-7/R-R	B	2,135±30(7ft)	Black	2,135-2,145mm																																																													
AT-S-26-8/8/B-10/R-R	C	3,050±60(10ft)	Black	3,050-3,060mm																																																													
AT-S-26-8/8/B-12/R-R	D	3,660±60(12ft)	Black	3,660-3,670mm																																																													
AT-S-26-8/8/B-14/R-R	E	4,270±60(14ft)	Black	4,270-4,280mm																																																													
AT-S-26-8/8/B-25/R-R	F	7,625±100(25ft)	Black	7,625-7,635mm																																																													
AT-S-26-8/8/B-50/R-R	G	15,250±150(50ft)	Black	15,250-15,260mm																																																													