

Technical drawing of a three-ribbed propeller. The drawing shows three views: a top view (left), a side view (middle), and a front view (right). The top view is labeled "M29XP1.5" and shows a propeller with three ribs. The side view is labeled "30 ON FLATS" and shows the propeller with a central hub and three ribs. The front view shows the propeller with three ribs. A dimension line at the bottom indicates a length of 33.5 [1.320]ref.

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020" DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex				
8						DRAWN	G.R.S.	03/28/08						
7						CHECKED			PART DESCRIPTION 7/16 FEMALE TO FEMALE ADAPTER					
6						ISSUED								
5						SHEET	1 OF 1							
4									PART NO. 272135					
3	CONTACT PIN	BER. COPPER	SILVER	1										
2	INSULATOR	TEFLON	NATURAL	1					DWG. NO. 272135.DWG REV. A SIZE A SCALE NA					
1	BODY	BRASS	NEXCOTE	1										
	DESCRIPTION	MATERIAL	FINISH	QTY		CAD FILE C:/272/272135.DWG								