




REV.	DATE	DESCRIPTION
NC	08/18/98	INITIAL RELEASE
A	01/23/07	UPDATE DRAWING FORMAT



RECOMMENDED
CABLE STRIPPING DIM'S



- NOTE:
- 1. CRIMPED FERRULE HEX CRIMP SIZE .429"
 - 2. CRIMPED CONTACT PIN HEX CRIMP SIZE .118"

8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020"	APPROVALS		DATE		Amphenol Connex						
7						DRAWN	G.R.S.	01/23/07								
6						CHECKED			PART DESCRIPTION BNC CRIMP JACK (FOR LMR400, BELDEN 8214, 9913, 9914)							
5						ISSUED										
4	FERRULE	COPPER	NICKEL	1		SHEET	1 OF 1		PART NO. 112603							
3	CONTACT PIN	PHOS. BRONZE	GOLD	1												
2	INSULATOR	TEFLON	NATURAL	1						DWG. NO. 112603.DWG						
1	BODY	BRASS	NICKEL	1												
DESCRIPTION					MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING		CAD FILE		C:/112/112603.DWG		REV. A	SIZE A	SCALE NA