





REV.	DATE	DESCRIPTION
NC	01/11/07	INITIAL RELEASE



RECOMMENDED
CABLE STRIPPING DIM'S



CRIMP NOTES:

1. CRIMPED FERRULE HEX CRIMP SIZE .429"
2. CRIMPED CONTACT PIN HEX CRIMP SIZE .118"

8					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007" .315 – 1.180 = ± 0.015" 1.180 – 4.724 = ± 0.020"	APPROVALS	DATE	Amphenol Connex					
7						DRAWN	G.R.S.						01/11/07
6						CHECKED			PART DESCRIPTION SMA REVERSE POLARITY CRIMP JACK (FOR BELDEN 9913, 9914, LMR400)				
5						ISSUED							
4	FERRULE	COPPER	GOLD	1		SHEET	1 OF 1		PART NO. 132332RP				
3	CONTACT PIN	BRASS	GOLD	1			DWG. NO. 132332RP.DWG						
2	INSULATOR	TEFLON	NATURAL	1								REV. A	
1	BODY	BRASS	GOLD	1			SIZE A						
	DESCRIPTION	MATERIAL	FINISH	QTY	DO NOT SCALE DRAWING							SCALE NA	
					C:/132/132332RP.DWG								