

					UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS; DIMENSIONS IN [] ARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY. UNLESS OTHERWISE SPECIFIED TOLERANCES FOR MILLIMETERS ARE: 0.5 – 8mm ± 0.20mm 8 – 30mm ± 0.40mm 30 – 120mm ± 0.50mm UNLESS OTHERWISE SPECIFIED TOLERANCES FOR INCHES ARE: .020 – .315 = ± 0.007” .315 – 1.180 = ± 0.015” 1.180 – 4.724 = ± 0.020” DO NOT SCALE DRAWING	APPROVALS		DATE		Amphenol Connex									
8						DRAWN	G.R.S.	09/17/07							PART DESCRIPTION SMA REVERSE POLARITY R/A CRIMP PLUG (FOR RG-316/U DOUBLE BRAID CABLE)				
7						CHECKED													
6	HEAT SHRINK TUBE		BLACK	1						PART NO. 132182RP									
5	FERRULE	COPPER	GOLD	1															
4	COVER	BRASS	GOLD	1						DWG. NO. 132182RP.DWG REV. NC SIZE A SCALE NA									
3	CONTACT PIN	BER. COPPER	GOLD	1															
2	INSULATOR	TEFLON	NATURAL	1															
1	HOUSING/BODY	BRASS	GOLD	1															
	DESCRIPTION	MATERIAL	FINISH	QTY	CAD FILE C:/132/132182RP.DWG														