

Seno Applicators

The Seno applicators offer a safe, clean and efficient alternative to processing in trays. Each applicator contains safe ready to use PCB chemistry. All work at room temperature, the chemistry being completely sealed in a container terminated by a sponge with a valve mechanism which dispenses precisely the right amount on each board. When not in use the sponge is protected by a cap. All applicators are waste free and when exhausted can be disposed of without the need for any special precautions. Each applicator contains safe to use chemistry and there is no need for special precautions when using them. The developers for instance being totally free from Sodium Hydroxide. Each applicator has a shelf life of at least two years. With the exception of etching the complete range of PCB processing sequence can be carried out with the applicators.



SN100 600-001	Photoresist applicator. Easy to apply, very quick drying positive working Photoresist for applying to uncoated laminates.
SN110 600-003	A universal developer applicator which develops all alkaline positive working resists.
SN111 600-002	Soft developer. As SN110 but weaker in strength making it ideal for use with freshly applied resists such as that contained in the SN100.
SN120 600-004	Resist strip applicator, quickly removes all remaining Photoresist from etched boards.
SN130 600-005	De-Ox applicator, removes all oxidisation from the etched copper circuit.
SN140 600-006	A flux applicator which applies a protective lacquer to a clean etched circuit, preventing any further oxidisation. Lacquer also acts as an excellent solder flux.



Mega Electronics Ltd.,

Mega House, Grip Industrial Estate,
Linton Cambridge, England. CB21 4XN

Tel: +44(0) 1223 893900 Fax: +44 (0) 1223 893894

Email: sales@megauk.com Web: www.megauk.com