

■ High temperature Lead-Free reflow Products

Endurance : 105 °C 1000 h

W.V.	Cap. (±20 %)	Case size			Specification			Part No. (RoHS:compliant)	Reflow	Min. Packaging Q'ty
		Dia.	Length	Size Code	Ripple Current (100 kHz) (+105°C) (mA r.m.s.)	$\tan \delta$ (120 Hz) (+20 °C)	Impedance (100 kHz) (+20 °C) (Ω)			Taping
(V)	(μ F)	(mm)	(mm)							(pcs)
6.3	22	4	5.4	B	60	0.26	3.00	EEEF0J220AR	(5)	2000
	47	5	5.4	C	95	0.26	1.80	EEEF0J470AR	(5)	1000
	68	6.3	5.4	D	140	0.26	1.00	EEEF0J680AP	(5)	1000
	100	6.3	5.4	D	140	0.26	1.00	EEEF0J101AP	(5)	1000
	220	8	6.2	E	230	0.26	0.40	EEEF0J221AP	(6)	1000
	330	8	10.2	F	450	0.26	0.30	EEEF0J331AP	(6)	500
	1000	10	10.2	G	670	0.26	0.15	EEEF0J102AP	(6)	500
	1500	10	10.2	G	670	0.26	0.15	EEEF0J152AP	(6)	500
10	33	5	5.4	C	95	0.19	1.80	EEEF1A330AR	(5)	1000
	100	8	6.2	E	230	0.19	0.40	EEEF1A101AP	(6)	1000
	150	8	6.2	E	230	0.19	0.40	EEEF1A151AP	(6)	1000
	220	8	10.2	F	450	0.19	0.30	EEEF1A221AP	(6)	500
	470	10	10.2	G	670	0.19	0.15	EEEF1A471AP	(6)	500
	1000	10	10.2	G	670	0.19	0.15	EEEF1A102AP	(6)	500
16	10	4	5.4	B	60	0.16	3.00	EEEF1C100AR	(5)	2000
	22	5	5.4	C	95	0.16	1.80	EEEF1C220AR	(5)	1000
	47	6.3	5.4	D	140	0.16	1.00	EEEF1C470AP	(5)	1000
	68	8	6.2	E	230	0.16	0.40	EEEF1C680AP	(6)	1000
	100	8	6.2	E	230	0.16	0.40	EEEF1C101AP	(6)	1000
	220	10	10.2	G	670	0.16	0.15	EEEF1C221AP	(6)	500
	330	10	10.2	G	670	0.16	0.15	EEEF1C331AP	(6)	500
	470	10	10.2	G	670	0.16	0.15	EEEF1C471AP	(6)	500
	680	10	10.2	G	670	0.16	0.15	EEEF1C681AP	(6)	500
25	6.8	4	5.4	B	60	0.14	3.00	EEEF1E6R8AR	(5)	2000
	22	6.3	5.4	D	140	0.14	1.00	EEEF1E220AP	(5)	1000
	33	6.3	5.4	D	140	0.14	1.00	EEEF1E330AP	(5)	1000
	47	8	6.2	E	230	0.14	0.40	EEEF1E470AP	(6)	1000
	68	8	10.2	F	450	0.14	0.30	EEEF1E680AP	(6)	500
	100	8	10.2	F	450	0.14	0.30	EEEF1E101AP	(6)	500
	220	10	10.2	G	670	0.14	0.15	EEEF1E221AP	(6)	500
	330	10	10.2	G	670	0.14	0.15	EEEF1E331AP	(6)	500
	470	10	10.2	G	670	0.14	0.15	EEEF1E471AP	(6)	500
35	1	4	5.4	B	60	0.12	3.00	EEEF1V1R0AR	(5)	2000
	2.2	4	5.4	B	60	0.12	3.00	EEEF1V2R2AR	(5)	2000
	3.3	4	5.4	B	60	0.12	3.00	EEEF1V3R3AR	(5)	2000
	4.7	4	5.4	B	60	0.12	3.00	EEEF1V4R7AR	(5)	2000
	6.8	5	5.4	C	95	0.12	1.80	EEEF1V6R8AR	(5)	1000
	10	5	5.4	C	95	0.12	1.80	EEEF1V100AR	(5)	1000
	22	6.3	5.4	D	140	0.12	1.00	EEEF1V220AP	(5)	1000
	33	8	6.2	E	230	0.12	0.40	EEEF1V330AP	(6)	1000
	47	8	6.2	E	230	0.12	0.40	EEEF1V470AP	(6)	1000
	100	10	10.2	G	670	0.12	0.15	EEEF1V101AP	(6)	500
	220	10	10.2	G	670	0.12	0.15	EEEF1V221AP	(6)	500
	330	10	10.2	G	670	0.12	0.15	EEEF1V331AP	(6)	500

- Please refer to the page of "Reflow Profile" and "The Taping Dimensions".
- When requesting vibration-proof product, please put the last "V" instead to "P"

Design and specifications are each subject to change without notice. Ask factory for the current technical specifications before purchase and/or use.
Should a safety concern arise regarding this product, please be sure to contact us immediately.

01 Mar. 2014