



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

Royal® 600V SOOW

Construction Parameters:

CONDUCTOR: 18 AWG - 10 AWG Class K stranded bare copper per ASTM B-174
INSULATION: EPDM
JACKET: CPE
COLOR: Black (Other colors available upon request)
PRINT LEGEND: SOUTHWIRE® ROYAL® (5 CROWN LOGO) CORD X/C XX AWG (X.XXmm2) SOOW E54864 (UL) 600V -40C TO 90C -- CSA LL39753 SOOW 600V -40C TO 90C FT2 WATER RESISTANT

INDENT LEGEND: P-07-KA070018-1-MSHA

PHYSICAL PROPERTIES:

TEMPERATURE RANGE: -40°C to 90°C

WATER RESISTANT: Yes

ELECTRICAL PROPERTIES:

VOLTAGE RATING: 600V rms, Max

Industry Approvals:

- o UL Standard 62
- o NEC Article 501.140 Class I Div. 2
- o NEC Article 400
- o CSA C22.2 No. 49
- o Passes CSA FT2 Flame Test
- o MSHA
- o EPA 40 CFR, Part 26, Subpart C, heavy metals per Table 1, TCLP method

Part Number	AWG	No. Cond.	Stranding	Insulation Wall, Nom.		O.D., Nom.		Net Weight		Amps*	Nom. DCR Ω/1M'	Nom. Lay Length in.	Color Code
822225	18	2	16/30	0.030	0.76	0.346	8.79	67	100	10	6.59	1.50	Black, White
822325	18	3	16/30	0.030	0.76	0.365	9.27	84	125	10	6.59	1.75	Black, White, Green
822425	18	4	16/30	0.030	0.76	0.390	9.91	98	146	7	6.59	2.00	Black, White, Red, Green
822226	16	2	26/30	0.030	0.76	0.370	9.40	81	121	13	4.05	1.75	Black, White
822326	16	3	26/30	0.030	0.76	0.390	9.91	94	140	13	4.05	2.00	Black, White, Green
822426	16	4	26/30	0.030	0.76	0.415	10.54	118	176	10	4.05	2.25	Black, White, Red, Green
822227	14	2	41/30	0.045	1.14	0.500	12.70	134	199	18	2.55	2.00	Black, White
822327	14	3	41/30	0.045	1.14	0.525	13.34	169	251	18	2.55	2.75	Black, White, Green
822427	14	4	41/30	0.045	1.14	0.570	14.48	201	299	15	2.55	3.25	Black, White, Red, Green
822228	12	2	65/30	0.045	1.14	0.570	14.48	184	274	25	1.61	2.50	Black, White
822328	12	3	65/30	0.045	1.14	0.595	15.11	224	333	25	1.61	3.00	Black, White, Green
822428	12	4	65/30	0.045	1.14	0.645	16.38	276	411	20	1.61	3.75	Black, White, Red, Green
822229	10	2	104/30	0.045	1.14	0.615	15.62	225	335	30	0.98	3.00	Black, White
822329	10	3	104/30	0.045	1.14	0.660	16.76	299	445	30	0.98	3.75	Black, White, Green
822429	10	4	104/30	0.045	1.14	0.710	18.03	360	536	25	0.98	4.25	Black, White, Red, Green

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

* Ampacity based on NEC Table 400.5(A) and CEC Table 12.

This product complies with European Directive 2002/95/EC (RoHS)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: June 24, 2014