

## PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 30208

**DESCRIPTION:** 3/0 AWG UL TYPE PPE CABLE

**CONSTRUCTION:** This cable consists of one bare copper conductor and TPE insulation and jacket.

**APPROVALS:** UL Type PPE, PPC/TPE CSA C22.2 No. 96, NEC Article 400., MSHA **APPLICATION:** 2000V Portable Wet Rated Submersible Outdoor Flexible Power Cable

**Construction Parameters:** 

Conductor 3/0 AWG Bare Copper

Stranding 19x88/30
Insulation Material TPE
Insulation Thickness 0.082" Nom.
Insulated Conductor Diameter 0.674" Nom.

Number of Conductors 1
Jacket Reinforcement Nylon Mesh Braid

Jacket MaterialTPEJacket Thickness0.113" Nom.Overall Cable Diameter0.900" Nom.Approximate Cable Weight784.0 Lbs/1M' Nom.

Flame Rating UL/CSA Horizontal Flame Test

**Electrical Properties:** 

Temperature Rating -50°C to 90°C Dry, 75°C Wet

Operating Voltage 2000V RMS Max.

DC Resistance per Conductor @ 20°C 0.062 Ohms/1M' Nom.

Max Ampacity per Conductor (Per NEC Table 400-5b) 350 amps/cond (Assume one current carrying conductor in free air)

Insulation Colors Black
Jacket Color Black

Legend (Indent) CCI SEOPRENE 3/0 AWG TYPE PPE E172226 (UL) 2000V 90C DRY 75C WET

 $\ensuremath{\text{C(UL)}}$  TYPE PPC/TPE 2000V -40C TO 105C 75C WET FT-5 SUNLIGHT RESISTANT

P-241-3-MSHA

Note: Type PPE cable is identical to Type W cable except it has TPE insulation and jacket.

Packaging will be Coleman's standard wooden reels with shrink-wrap over the cable.

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: October 14, 2011