

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 51011

DESCRIPTION: 18 AWG STRANDED TFFN FIXTURE WIRE

CONSTRUCTION: This cable consists of one bare copper insulated conductor. **APPROVALS:** UL 66 - Fixture Wire; CSA C22.2 No. 127 - Lead Wire

APPLICATION: Fixture Wire; Equipment and Lead Wire

Construction Parameters:

Conductor 18 AWG Bare Copper

Stranding 16/30
Insulation Material PVC/Nylon
Insulation Thickness 0.016" Nom.
Nylon Insulation Thickness 0.005" Nom.
Insulated Conductor Diameter 0.088" Nom.
Approximate Cable Weight 7.5 Lbs/1M' Nom.

Electrical & Environmental Properties:

Temperature Rating -20°C to 90°C

Operating Voltage 600 V RMS Max., 1000V (AWM 1452)

DC Resistance per Conductor @ 20^oC 6.49 Ohms/1M' Nom.

Insulation/Jacket Color Varies (Consult factory for availability)

Legend (Surface Ink Print) CCI TRIANGLE 18 AWG (0.82mm²) TFFN E22337 (UL) 600V OR AWM STYLE 1316 &

1408 600V & 1452 1000V GASOLINE & OIL RESISTANT I OR MTW -- 156016 CSA

TEWN 600V 105C FT1

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: March 14, 2014