



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: F54604
DESCRIPTION: 8 AWG SOLID UNINSULATED CABLE
CONSTRUCTION: This cable consists of one bare copper uninsulated conductor.
APPROVALS: ASTM B3

Construction Parameters:

Conductor	8 AWG Bare Copper
Stranding	Solid
Conductor Diameter	0.129" Nom.
Number of Conductors	1

Electrical & Enviromental Properties:

DC Resistance per Conductor @ 20°C	0.63 Ohms/1M' Nom.
------------------------------------	--------------------

On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____

Specification Issue Date: February 20, 2009