


PRODUCT SPECIFICATION

<i>DATE</i>	<i>REV</i>	<i>ECN</i>	<i>DESCRIPTION</i>
9/17/2007	A	18489	SPECIFICATION CREATED

Parent Number: F08023-

Description: 8 19/.0295 BC MTW or BC-5W2 or THHW or AWM 1011/1028/1231 or 1032 TEW or AWM I A/B OD 0.247"

DIAMETER: 0.247
TOLERANCE ±: 0.003



MIN AVERAGE WALL: 0.045

MINIMUM WALL: 0.040

Stranding: 19/.0295 BC LHL

Style: UL: MTW or BC-5W2 or AWM 1011/1028/1231 or 1032 CSA: TEW or AWM I A/B

Insulation: PVC

Print Legend: 8 AWG (8.37mm²) E125352 (PLANT ID CODE) (UL) BC-5W2 OR MTW OR THHW OR AWM 1011/1028/1231/1344 600V OR 1032 1000V MOISTURE RESISTANT OIL RES I SUN RES VW-1 -- 156016 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

Voltage: 600V, 1032=1000V

Temperature: 105C

Notes:

This product complies with European Directive 2002/95/EC (RoHS)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Approval:

Customer Part Nbr(s): _____

Approved By: _____ **Date:** _____

Title: _____ **Company Name:** _____

COLEMAN CABLE, INC

1530 Shields Drive
Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com

