## **PRODUCT SPECIFICATION**

I	DATE	REV	<b>ECN</b>	<b>DESCRIPTION</b>
	12/1/2009	I	CCI# 12369	SPECIFICATION UPDATED


Parent Number: F18082-

**Description:** 18 16/30 TC AWM 3173 or 3237 CL 1251

AWM I A/B

**DIAMETER:** 0.108

 $TOLERANCE \pm : 0.003$ 



Stranding: 16/30 TC LHL

Style: UL: AWM 3173 or 3237 CSA: CL 1251 AWM I A/B

MIN AVERAGE WALL: 0.030 MINIMUM WALL: 0.027

Insulation: XLPE

<u>Print Legend:</u> 18 AWG (0.823mm2) E96824 (PLANT ID CODE) (AWM LOGO) AWM 3173 125C 600V OR 3237 105C 1000V XLPE -- 156016 CSA CL1251 125C 600V FT2 OR AWM I A/B 125C 600V FT2 -- SUITABLE FOR "SWITCHBOARD WIRE" -- MADE IN USA

Voltage: UL: AWM 3173 = 600V, AWM 3237 = 1000V CSA: AWM/CL1251 = 600V, AWM = 1000V

Temperature: <u>UL: AWM 3237 = 105C, AWM 3173 = 125C</u> <u>CSA:</u> AWM = 105C, CL1251 or AWM = 125C

Notes:

This product complies with European Directive 2002/95/EC (RoHS)

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer	Ap	pro	val	<b>!</b> :
	_	_		

Customer Part Nbr(s):				
Approved By:				
Title:	Company Name:			

## COLEMAN CABLE, INC

1530 Shields Drive Waukegan, IL 60085

Phone: 1-800-323-9355

www.colemancable.com