



PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 94564
DESCRIPTION: 16/4 STRANDED CM/CL3/FPL/PLTC DIRECT BURIAL SOUND AUDIO CABLE
CONSTRUCTION: This cable consists of four bare copper insulated conductors and an overall jacket.
APPROVALS: UL Standard 13 & 444 & 1424 NEC Articles 725 & 760 & 800
APPLICATION: General Purpose Direct Burial Power Limited Circuit, Tray and Communications Cable Used in Audio Applications
Fire Alarm Power Limited Circuit Cable Used in General Purpose Applications for Addressable Fire Alarm Systems

Construction Parameters:

Cable Cross-Section

Conductor	16 AWG Bare Copper
Stranding	65/34
Insulation Material	PVC
Insulation Thickness	0.010" Nom.
Insulated Conductor Diameter	0.078" Nom.
Number of Conductors	4
Lay Length	3.00" Nom.
Core Wrap	None
Jacket Material	PVC
Jacket Type	Tubed
Jacket Thickness	0.020" Nom.
Overall Cable Diameter	0.226" Nom.
Approximate Cable Weight	46.5 Lbs/1M' Nom.
Flame Rating	UL 1581 Vertical Tray Flame Test



Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
Capacitance Between Conductors @ 1 KHz	39 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	-----
DC Resistance per Conductor @ 20°C	4.06 Ohms/1M' Nom.

Insulation Colors	Black Red White Green
Jacket Color	Varies (Consult Factory)

Legend (Surface Ink Print)	COLEMAN CABLE 94564 16 AWG 4/C C(ETL)US (ETL CODE) TYPE CM/CL3/FPL/PLTC DIRECT BURIAL AUDIO CABLE SUN RES -- TYPE CMH FT1
----------------------------	--

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

Cable has a rip cord for easy jacket removal. The jacket is sequentially footmarked.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 6, 2014