



PRODUCT DATA SHEET

Controlled Document - Engineering Drive


1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 95215
DESCRIPTION: 16/2 STRANDED SHIELDED CMR/CL3R/FPLR FT4 CABLE
CONSTRUCTION: This cable consists of two bare copper insulated conductors with an overall shield with a drain. The overall assembly has an overall jacket.
APPROVALS: UL Standard 13 and 444, NEC Articles 725 and 800.
APPLICATION: Class 3 Power Limited Circuit Cable and Communications Cable for Riser Applications

Construction Parameters:

Conductor	16 AWG Bare Copper
Stranding	19/.0117"
Insulation Material	PVC
Insulation Thickness	0.008" Nom.
Insulated Conductor Diameter	0.074" Nom.
Number of Conductors	2
Lay Length	4.00" Nom.
Shield	Alum/Mylar
Drain	24 AWG Solid Tinned Copper
Jacket Material	PVC
Jacket Thickness	0.017" Nom.
Overall Cable Diameter	0.191" Nom.
Approximate Cable Weight	31.7 Lbs/1M' Nom.
Flame Rating	UL 1666 Riser Flame Test

Cable Cross-Section



Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.
Capacitance Between Conductors @ 1 KHz	71 pF/ft Nom.
Capacitance Between Conductors to Shield @ 1 KHz	130 pF/ft Nom.
DC Resistance per Conductor @ 20°C	3.92 Ohms/1M' Nom.

Insulation Colors	Black Red
Jacket Color	Gray (Other colors available for minimum order)

Legend (Surface Ink Print) COLEMAN CABLE 95215 16 AWG 2/C C(ETL)US (ETL CODE) TYPE CMR/CL3R/FPLR
SUN RES --- CMX OUTDOOR --TYPE CMG FT4 -- XX/XX/XX (MONTH/DAY/YEAR) XXXXXX
(W/O #) P-07-KA120011-MSHA 300V

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: September 12, 2013