



# PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 920414

**DESCRIPTION:** RG-6 QUAD SHIELDED COAXIAL CABLE WITH TWO FOILS PLUS 40% AND 60% ALUMINUM BRAIDS FOR HIGH DEFINITION TELEVISION APPLICATIONS

**RATING:** ETL DUAL LISTED AS CM/CL2 AND CATV

### Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	18 AWG (1/.040) Solid Bare Copper		0.040
Dielectric:	Foam Polyethylene color natural	0.070	0.180
Shielding 1 & 2:	100% Bonded Polyester/Aluminum Tape plus 40% Aluminum Braid		0.216
Shielding 3 & 4:	100% Polyester/Aluminum Tape plus 60% Aluminum Braid		0.249
Jacket:	PVC	0.029	0.295

### Electrical Properties:

	<u>VALUE*</u>
Impedance (ohms):	75
Capacitance (pF/ft):	17
Velocity of Propagation (%):	81
Attenuation (db/100 ft):	
10 MHz	0.9
50 MHz	1.46
100 MHz	1.85
200 MHz	2.70
400 MHz	3.90
700 MHz	5.30
1000 MHz	6.50
1500 MHz	8.50
2000 MHz	9.45
2500 MHz	10.50
3000 MHz	11.40

### Cable Cross-section:

(NOT TO SCALE)



### Miscellaneous Information:

Jacket Color:	Black or White or Gray
Jacket Print (Aqua/Blue): (Sequentially footprinted)	CCI 920414 RG6 18 AWG BC QUAD SHIELD 40/60% AL BRAID (ETL) 3020454 CM OR CL2 OR CATV 75C SUN RES SWEPT TO 3.0 GHZ
Applicable NEC Article:	725, 800 & 820
Flame Rating:	UL-1581 Vertical Tray Flame Test
Maximum Operating Temperature:	75° C
Approximate Weight (lb/1000 ft):	33

*This product complies with European Directive 2011/65/EU (RoHS-2)*

*The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.*

Issued: 1/18/13

\* = Nominal value  
By: RBC