



# PRODUCT DATA SHEET

Controlled document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 92094

**DESCRIPTION:** COMBO RG59 COAXIAL PLUS 18 AWG/2 CONDUCTOR IN ONE JACKET

**RATING:** UL LISTED AS CL2  
UL SUNLIGHT RESISTANT  
UL RECOGNIZED COMPONENT AWM STYLE 1354

### Construction Parameters:


		<b>OD (in)*</b>
<u>Part 1:</u>	Conductor: 20 AWG (1/.032) Solid Bare Copper	0.032
	Dielectric: Foam Polyethylene color natural	0.144
	Shielding: 95% Copper Braid	0.171
	Jacket: PVC	0.239
<u>Part 2:</u>	Conductor: 18 AWG (16/30) Solid Bare Copper	0.045
	Dielectric: PVC	0.065
<u>Final:</u>	Jacket: One Part 1 and 2 Part 2's are jacket under one jacket.	0.340

### Electrical Properties:

	<b>VALUE*</b>
<u>Coax:</u>	
Impedance (ohms):	75
Capacitance (pF/ft):	17
Velocity of Propagation (%):	78
Attenuation** (db/100 ft):	
50 MHz	1.7
216 MHz	3.6
240 MHz	3.8
260 MHz	4.0
270 MHz	4.0
300 MHz	4.3

### Cable Cross-section:

(NOT TO SCALE)



### Miscellaneous Information:

Coax Jacket Color: Black  
 Coax Jacket Print (White): RG 59/U 20 AWG TYPE CL2 (UL) OR AWM 1354 E100316-I  
 Final Jacket Color: White  
 Final Jacket Print (Black): CCI 92094 E100316-I 18 AWG/2C & 20 AWG/1C RG 59/U COAX TYPE CL2 (UL) SUN RES

Applicable NEC Article: 725 & 310  
 Flame rating: UL-1581 Vertical Tray Flame Test  
 Sunlight Resistant: UL-13 Sunlight Resistant Test  
 Approximate Weight (lb/1000 ft): 65

This product complies with European Directive 2011/65/EU (RoHS-2)  
 On special orders the customer will accept all factory lengths and  $\pm 10\%$  of total order requested.  
 A rip cord is added to facilitate jacket removal.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

