



# PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 921015  
**DESCRIPTION:** RG-6/U PLENUM COAXIAL CABLE WITH FOIL AND 80% BRAID SWEPT TO 3.0 GHZ  
**RATING:** C(ETL)US LISTED AS CMP/CL2P FT6

## Construction Parameters:


		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	18 AWG (1/.040) Copper Clad Steel		0.040
Dielectric:	Foam FEP color natural	0.065	0.170
Shielding:	Aluminum/Polyester/Aluminum Foil with 80% Aluminum Braid		0.194
Jacket:	Low Smoke PVC	0.021	0.235

## Electrical Properties:

	<u>VALUE*</u>
Conductor Resistance (ohms/Kft):	16.3
Impedance (ohms):	75
Capacitance (pF/ft):	16.5
Velocity of Propagation (%):	82
Attenuation (db/100 ft):	
50 MHz	1.5
100 MHz	1.9
200 MHz	3.2
400 MHz	4.2
700 MHz	6.4
1000 MHz	6.9
1500 MHz	9.4
2000 MHz	11.1
2200 MHz	11.8
3000 MHz	17.0

## Cable Cross-section:

(NOT TO SCALE)



## Miscellaneous Information:

Jacket Color: Natural  
Jacket Print (Teal/Aqua): CCI 921015 RG6 18 AWG CCS DUAL SHIELD 80% AL BRAID C(ETL)US  
ASCENDING/DESCENDING FOOTAGE MARKING 3020464 CMP OR CL2P FT6 75C SWEPT TO 3.0 GHZ  
Applicable NEC Article: 725 & 800  
Temperature Rating: 75C  
Flame Rating: UL 910 Steiner Tunnel Smoke and Flame Test  
CSA FT6 Horizontal Flame and Smoke Test  
Approx. Weight (lb/1000 ft): 42

*This product complies with European Directive 2002/95/EC (RoHS)*

*On special orders the customer will accept all factory lengths and ± 10% of total order requested.*

*The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product (s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise*

Issued: 09/20/06

\* = Nominal value  
By: PMV