



PRODUCT DATA SHEET

Controlled Document – Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 921019

DESCRIPTION: RG-6/U QUAD PLENUM COAXIAL CABLE WITH TWO FOILS AND 60%/40% ALUMINUM BRAIDS

RATING: ETL LISTED AS CL2P
C(ETL) CERTIFIED AS CMP FT6

Construction Parameters:

		<u>Wall (in)*</u>	<u>OD (in)*</u>
Conductors:	18 AWG (1/.040) Copper Clad Steel		0.040
Dielectric:	Foam FEP color natural	0.064	0.168
Shielding 1 & 2:	Bonded Aluminum/Polyester/Aluminum Foil with 60% Aluminum Braid		0.202
Shielding 3 & 4:	Aluminum/Polyester/Aluminum Foil with 40% Aluminum Braid		0.234
Jacket:	Low Smoke PVC	0.017	0.268

Electrical Properties:

	<u>VALUE*</u>
Conductor Resistance (ohms/Kft):	32
Impedance (ohms):	75
Capacitance (pF/ft):	16.5
Velocity of Propagation (%):	82
Attenuation (db/100 ft):	
50 MHz	1.5
100 MHz	2.4
200 MHz	3.2
400 MHz	4.8
600 MHz	6.2
900 MHz	7.9
2200 MHz	14.7
3000 MHz	18.2

Cable Cross-section:

(NOT TO SCALE)



Miscellaneous Information:

Jacket Color:	Natural & Black
Jacket Print (Teal/Aqua):	CCI 921019 RG6 18 AWG CCS QUAD SHIELD 65/40% AL BRAID C(ETL)US 3020465 CMP
ASCENDING/DESCENDING FOOTAGE MARKING	OR CL2P FT6 75C SWEPT TO 3.0 GHZ
Applicable NEC Article:	725 & 800
Flame Rating:	UL 910 Steiner Tunnel Smoke and Flame Test CSA FT6 Horizontal Flame and Smoke Test
Maximum Pulling Tension	110 lbs
Approx. Weight (lb/1000 ft):	32

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and $\pm 10\%$ of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

Connector: Corning Gilbert GF-6-AHS/USA

Issued: 05/16/07

* = Nominal value
By: PEP