

# PRODUCT DATA SHEET

Controlled Document - Engineering

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

**PART NUMBER:** 992153

RG-11/U COAXIAL CABLE WITH FOIL SHIELD AND 60% **DESCRIPTION:** 

ALUMINUM BRAID

**RATING:** ETL DUAL LISTED AS CM/CL2 AND CATV

### Construction Parameters:

		Wall (in)*	OD (in)*
Conductors:	14 AWG (1/.064) Solid Bare Copper		0.064
Dielectric:	Foam Polyethylene color natural	0.110	0.285
Shielding:	Fusible Aluminum/Polyester/Aluminum foil with 60% Aluminum Braid		0.321
Jacket:	PVC	0.042	0.405

## **Electrical Properties:**

## Cable Cross-section:

(NOT TO SCALE)

		<u>VALUE*</u>
Conductor Resistance (ohms/mft):		2.6
Impedance (ohms):		75
Capacitance (pF/ft):		17.3
Velocity of Propagation (%):		78
Attenuation (db/100 ft):	50 MHz	1.0
	100 MHz	1.3
	200 MHz	1.8
	400 MHz	2.5
	700 MHz	3.5
	1000 MHz	4.2
	1400 MHz	5.1
	2000 MHz	6.2



#### Miscellaneous Information:

Jacket Color:

Jacket Print (White): CCI 992153 RG11 14 AWG BC DUAL SHIELD 60% AL BRAID (Sequentially footprinted) E118963 (UL) CM OR CL2 OR CATV 75C SUN RES SWEPT TO

3.0 GHZ

Applicable NEC Article: 725 and 820

Flame Rating: UL-1581 Vertical Tray Flame Test

75 ° C Maximum Temperature Rating: Approximate Weight (lb/1000 ft): 60

Issued:

09/21/06

Company Name:		
Customer Approval:	Date:	

This product complies with European Directive 2002/95/EC (RoHS)

On special orders the customer will accept all factory lengths and  $\pm$  10% of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We reserve the right to review and modify all constructions to conform with the latest Regulatory requirement. We disclaim all liability in connection with the use of information contained herein or otherwise. This specification is propriety intellectual property of COLEMAN CABLE. Any information contained herein shall not be disclosed to any party without written consent of COLEMAN CABLE.