



PRODUCT DATA SHEET


Controlled Document - Engineering Drive

1530 Shields Drive
Waukegan, IL 60085
Toll-Free (800) 323-9355
Fax: (847) 689-1192

PART NUMBER: 099273
DESCRIPTION: 24/4PR CAT5e CMR, 2 QUAD SHLD CM COAX, OPTICAL FIBER MEMBER WITH A JACKET
CONSTRUCTION: This cable consists of two standard 24/4 pair Category 5e cables, two standard 60/40 quad shield coax cables, and a multimode fiber optic cable cabled together with a tubed PVC jacket.
APPROVALS: UL Standard 13 & 444, NEC Article 725 & 800. Overall cable is rated CM.
APPLICATION: Designed for home audio and theatre applications.

Construction Parameters:

Cable 1	Blue 24/4PR Cat 5e
Cable 2	Gray 24/4PR Cat 5e
Cable 3	Black 18ga Quad Shielded RG 6/U Coax
Cable 4	White 18ga Quad Shielded RG 6/U Coax
Cable 5	Orange 62.5 μ m Fiber Cable (x2)
Diameters	
Cable1	0.200" Nom.
Cable 2	0.200" Nom.
Cable 3	0.295" Nom.
Cable 4	0.295" Nom.
Cable 5	0.114" Nom.
Lay Length	12.00" Nom.
Overall Jacket Material	PVC
Overall Jacket Thickness	0.030" Nom.
Overall Cable Diameter	0.670" Nom.
Approximate Cable Weight	156.5 Lbs/1M' Nom.
Flame Rating	UL 1581 Tray Test



Electrical Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	300 V RMS Max.

Note: See data sheets for Coleman parts 96263 and 92041 for complete electrical information.

Internal Cable Colors	Cat 5e: Blue and Gray Coax: Black and White Fiber: Orange
Jacket Color	Orange
Legend on Cat 5e	CAT5E COLEMAN CABLE 96263 CAT 5E 24 AWG C(ETL)US LISTED 2003548 TYPE CMR FT-4 VERIFIED TO EIA/TIA 568-B.2 CAT 5E TESTED TO 350 MHZ CAT 5E
Legend on Coax	COLEMAN CABLE 92041 RG 6/U QUAD SHIELD SWEPT TO 3.0 GHZ 18 AWG TYPE CL2 75C (ETL) 3020454 OR CATV SUN RES
Legend on Fiber	COLEMAN CABLE P/N 099272 2-FIBER 62.5/125 RISER 2.9MM INTERCONNECT CABLE E188900 c(UL)US OFNR OFN-FT4 (UL) VERIFIED TO BELLCORE GR-409-CORE TIA/EIA-568-B ISO/IEC-11801 ZZ/TT (JOB#) XXXXX FEET
Legend on Overall Jacket (Surface Ink Print)	COLEMAN CABLE 099273 (ETL)US 3023226 TYPE CM 2 X 24/4PR CAT5 & 2 X 18 AWG RG6 QUAD & 62.5 μ m MULTIMODE FIBER -- W/O #

Packaging Standard plywood reels with shrink wrap protection.

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The jacket is sequentially footmarked and has a rip cord.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Name _____

Customer Approval _____ Date: _____

Specification Issue Date: January 7, 2013