

PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 7310

DESCRIPTION: ACCESS CONTROL 4 COMPONENT JACKETED CMP/CL3P/FPLP

APPROVALS: ETL Listed to UL 444.

Construction Parameters:

 Coleman Cable Similar P/N
 72321
 72344
 75366
 71944

 AWG / Quantity
 22/2
 22/4
 22/6 Shielded
 18/4

 Cable Dia.
 0.110"
 0.127"
 0.191"
 0.166"

Cabling lay length12" Nom.Jacket MaterialLow Smoke PVCJacket Thickness0.017" Nom.Overall Cable Diameter0.393"

Other Parameters

Temperature Rating 75°C

Voltage Rating 300 V RMS Max.

Inner Jacket Color White Blue Orange Gray

Legend - Inner Jackets 22/2 - 72321 CCI 72321 22 AWG 2/C C(ETL) US (ETL CODE) TYPE CMP/CL3P/FPLP

75C -- TYPE CMP FT 6 -- DOOR CONTACT

22/4 - 72344 CCI 72344 22 AWG 4/C C(ETL) US (ETL CODE) TYPE CMP/CL3P/FPLP

75C -- TYPE CMP FT6 -- REQUEST TO EXIT/SPARE

22/6 Shielded - 75366 CCI 75366 22 AWG 6/C C(ETL) US (ETL CODE) TYPE CMP/CL3P/FPLP

75C -- TYPE CMP FT 6 -- CARD READER

18/4 - 71944 CCI 71944 18 AWG 4/C C(ETL) US (ETL CODE) TYPE CMP/CL3P/FPLP

75C -- TYPE CMP FT6 -- LOCK POWER

Legend - Outer Jacket CCI 73101 ACCESS CONTROL 4 COMPONENT C(ETL)US

(ETL CODE) CMP/CL3P/FPLP 75C -- TYPE CMP FT6 $\,$

This product complies with European Directive 2002/95/EC (RoHS)

The customer will accept all factory lengths and +/- 10 percent of total order requested.

 $\label{lem:cable} \textbf{Cable has a rip cord for easy jacket removal.} \ \ \textbf{The jacket is sequentially footmarked}.$

Material is not returnable and purchase order is non-cancelable after production has been started or special materials have been ordered.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: December 5, 2013