



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 96273  
**DESCRIPTION:** 24 AWG /4 Pair Category 5e F/UTP CMR  
**COMPLIANCE:**

- ETL Listed Type CMR
- C(ETL) listed CMR FT4
- ETL Verified to TIA/EIA 568-C.2
- Tested to 350 MHz

## Construction Parameters:

Conductor 24 AWG Solid Bare Copper  
Dielectric Solid PE  
Assembly Each pair has different lay length for cross-talk prevention  
Shielding Aluminum/polyester foil with 26 solid TC drain wire  
Jacket PVC

### DIAMETER\*

0.020"  
0.039"

0.244"

\* = Nominal value

## Product Electrical Characteristics:

Max Capacitance (nF/100m @ 1 kHz)	Max DC Resistance (Ω/100m @ 20 °C)	Max Delay Skew (ns/100m)	Nom Velocity of Propagation (%)	Characteristic Impedance (Ω @ 1-100 MHz)
5.6	9.38	45	68	100 +/- 15

Freq (MHz)	Max Insertion Loss (dB/100m)	Min NEXT Loss (dB)	Min PSNEXT Loss (dB)	Min ACR (dB/100m)	Min PSACR (dB/100m)	Min ACRF (dB/100m)	Min PSACRF (dB/100m)	Min Return Loss (dB)
1	2.0	65.3	62.3	63.3	60.3	63.8	60.8	20
10	6.5	50.3	47.3	43.8	40.8	43.8	40.8	25
16	8.2	47.3	44.3	39.1	36.1	39.7	36.7	25
20	9.3	45.8	42.8	36.5	33.5	37.7	34.7	25
31.25	11.7	42.9	39.9	31.2	28.2	33.9	30.9	23.6
62.5	17.0	38.4	35.4	21.4	18.4	27.8	24.8	21.5
100	22.0	35.3	32.3	13.3	10.3	23.8	20.8	20.1
155	28.1	32.4	29.4	4.3	1.3	20.0	17.0	18.8
200	32.4	30.8	27.8	-	-	17.8	14.8	18.0
250	36.9	29.3	26.3	-	-	15.8	12.8	17.3
350	44.9	27.1	24.1	-	-	12.9	9.9	16.3

\* Note that values above 100 MHz are not guaranteed and are for engineering reference only.

Pair Colors: White with Blue, White with Orange, White with Green, White with Brown  
Jacket Color: Standard colors are Blue and Gray

Legend (Ink Print) COLEMAN CABLE 24 AWG 4PR CATEGORY 5E F/UTP C(ETL)US LISTED (ETL CODE) TYPE CMR SUN  
RES -- ETL VERIFIED TO TIA/EIA-568-C.2 CAT 5E

(Also printed with sequential footage & date code)

This product complies with European Directive 2011/65/EU (RoHS-2)

On special orders, the customer will accept all mil lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control, all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of product(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: April 12, 2013