

## PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive Waukegan, IL 60085 Toll-Free (800) 323-9355 Fax: (847) 689-1192

PART NUMBER: 42238

**DESCRIPTION:** 12-2 W/GND THW FLAT BONDED PUMP CABLE

**CONSTRUCTION:** This cable consists of two bare copper insulated conductors and a ground laid parallel and bonded together.

APPROVALS: UL Standard 83, Type THW

**APPLICATION:** Underwater Pumps and Similar Applications

## **Construction Parameters:**

Conductor 12 AWG Bare Copper

Stranding 19/.0185
Insulation Material PVC
Insulation Thickness 0.047" Nom.
Insulated Conductor Diameter 0.183" Nom.

Number of Conductors 2

Ground Wire 12 AWG 19 Strand PVC Insulated

Lay Length Parallel

Approximate Cable Weight 98.0 Lbs/1M' Nom.

## **Electrical Properties:**

Temperature Rating -20°C to 75°C
Operating Voltage 600 V RMS Max.
Capacitance Between Conductors @ 1 KHz 37 pF/ft Nom.
DC Resistance per 2 AWG Conductor @ 20°C 1.58 Ohms/1M' Nom.

Insulation Colors Black Red Green

Legend (Surface Ink Print on Black Conductor) CCI E101736 \* 12 AWG (3.31mm²) (UL) 600 VOLTS TYPE THW INS.

SUBMERSIBLE PUMP CABLE

This product complies with European Directive 2002/95/EC (RoHS)

The customer will accept all factory lengths and +/- 10 percent of total order requested. The jacket is sequentially footprinted from 2 to the footage designated by the put-up code.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: August 6, 2008