



# PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive  
Waukegan, IL 60085  
Toll-Free (800) 323-9355  
Fax: (847) 689-1192

**PART NUMBER:** 55560  
**DESCRIPTION:** 14 AWG SOLID W/GND UF-B CABLE  
**CONSTRUCTION:** This cable consists of two bare copper insulated conductor and one bare ground laid parallel with an overall jacket.  
**APPROVALS:** UL Standard 493  
**APPLICATION:** Underground Feeder Cable for Direct Burial Applications

---

## Construction Parameters:

Conductor	14 AWG Bare Copper
Ground	14 AWG Bare Copper
Stranding	Solid
Insulation Material	PVC/Nylon
Insulation Thickness	0.021" Nom.
Insulated Conductor Diameter	0.106" Nom.
Number of Conductors	2
Number of Grounds	1
Jacket Material	PVC
Jacket Thickness	0.048" Nom.
Overall Dimensions	0.210" x 0.400" Nom.

---

## Electrical & Environmental Properties:

Temperature Rating	-20°C to 60°C
Operating Voltage	600 V RMS Max.
DC Resistance per Conductor @ 20°C	2.54 Ohms/1M' Nom.

---

Insulation Colors	Black White Bare Ground
Jacket Color	Gray

On special orders, the customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman Cable's standard terms and conditions contained therein, including without limitation Coleman Cable's standard warranty. Coleman Cable disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Specification Issue Date: January 5, 2014