




PRODUCT SPECIFICATION

CATALOG NUMBER: See table below
DESCRIPTION: SJTW and STW twist-to-lock extension cords
APPROVALS: UL Listed

CONSTRUCTION PARAMETERS:

Cord type: See table below
Conductors: 12/3, 65/30 BC
Jacket material: PVC, yellow
Overall cable O.D. (nom): See table below
Cord rating per the NEC: See table below
Attachment plug configuration: NEMA L5-20P
Cord connector configuration: NEMA L5-20R
Plug and cord connector material: PVC, black



Note: Plug style may vary

ELECTRICAL PROPERTIES:

Cable temperature rating: -40 to +60 °C
Nominal operating voltage: 125 VAC
Maximum operating current: See table below

Catalog number	Length	Cord type	Cord rating	Cable O.D. (nom)	Current rating
09208	50 ft	SJTW	Hard usage	0.420 in	20A
09209	100 ft				15A
09028	50 ft	STW	Extra hard usage	0.585 in	20A
09029	100 ft				15A

The information presented here is, to the best of our knowledge, true and accurate. However, since conditions of use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable Inc. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable Inc.