



Feature

1. Built-in controller - 'Toshiba (T6963C)'
2. 1/128 duty cycle.
3. Built-in N/V
4. 5 V Operating Voltage

Pin Assignment

Pin	Symbol	Function
1	FG	Frame GND
2	Vss	GND
3	Vdd	+5V
4	Vo	Scan Start-up signal
5	WR	Frame reverse signal (alternate signal)
6	RD	Data latch epsule
7	CE	Display Enable pulse
8	C/D	Data Shift pulse
9	RST	Display Data signal
10-17	DB0-DB7	Data bus line
18	F S	Control Voltage

Mechanical Data

Item	Standard Value	Unit
Module Dimension	144.0 x 104.0	mm
Viewing Area	114.0 x 64.0	mm
Dot Size	0.43 x 0.43	mm
Dot Pitch	0.45 x 0.45	mm

Absolute Maximum Rating

Item	Symbol	Standard Value			Unit
		min.	typ.	max.	
Power Supply	VDD-VSS	4.75	5.0	5.25	V
Input Voltage	VI	-0.3	--	VDD	V

Note: VSS=0 Volt, VDD=5.0 Volt.

Electronical Characteristics

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD	L level	0.7V _{DD}	--	VDD	V
	VIO	H level	--	--	0.3V _{DD}	V
Supply Current	IDD	VDD=+5V	0	55	60	mA
Recommended LC Driving Voltage for Normal Temp. Version module	VDD-V0	0°C	20.3	21.4	22.5	V
		25°C	18.0	19.1	20.2	
		50°C	17.8	18.9	20.0	
LED Forward Voltage	VF	25°C	--	4.2	--	V
LED Forward Current	IF	25°C	--	900	1800	mA
CCFL	VF	25°C	--	250	590	V _{rms}
	IF	25°C	--	--	5.5	mA
EL	---	---	--	--	5.0	mA