



### Feature

1. 320x240 dots
2. +5V power supply
3. 1/240 duty cycle
4. No controller
5. Touch panel option (analog type)

### Mechanical Data

Item	Standard Value	Unit
Module Dimension	142.0 x 96.0	mm
Viewing Area	104.0 x 79.3	mm
Active Area	95.97 x 71.97	mm
Dot Size	0.27 x 0.27	mm
Dot Pitch	0.3 x 0.3	mm

### Pin Assignment

Pin	Symbol	Function
1	FRAME	First Line marker
2	DF	alternate signal
3	LOAD	Data latch
4	CP	Data shift
5	DISPOFF	H:ON L:OFF
6	DB0	Data bus line
7	DB1	Data bus line
8	DB2	Data bus line
9	DB3	Data bus line
10	Vdd	Power supply for LOGIC
11	Vss	GND
12	Vee	Negative Voltage
13	Vo	Operating voltage LCD driving
14	FG	Fix hole ground

### Absolute Maximum Rating

Item	Symbol	Standard Value			Unit
		min.	typ.	max.	
Power Supply	VDD-VSS	4.75	5.0	5.25	V
Input Voltage	VI	-0.3	--	VDD	V

Note: VSS=0 Volt, VDD=5.0 Volt.

### Electronical Characteristics

Item	Symbol	Condition	Standard Value			Unit
			min.	typ.	max.	
Input Voltage	VDD	L level	0.7V <sub>DD</sub>	--	V <sub>DD</sub>	V
	VIO	H level	0	--	0.3V <sub>DD</sub>	V
Supply Current	IDD	VDD=+5V	--	10.0	15.0	mA
Recommended LC Driving Voltage for Normal Temp. Version module	VDD-V0	0°C	22.0	23.0	24.0	V
		25°C	21.3	22.2	23.0	
		50°C	19.5	20.8	22.1	
CCFL Starting Voltage	VFLS	25°C	--	600	--	Vrms
CCFL Driving Voltage	VFLD	25°C	--	268	--	Vrms
CCFL Driving Current	IFLD	VFQ=450Vrms 30KHZ	--	5.0	--	mA <sub>rms</sub>