

PTC40 Series

40 Watts

Single Output Switching Power Supply



Features:

- * Ultra-Compact 3.0 x 1.5 x 1.1" Open Frame Package
- * Universal AC Input - EN61000-3-2 Compliance
- * 40 Watts with 5 cfm Airflow / 28 Watts Convection Cooled
- * Less than 0.3W No Load Input Power
- * 100,000 hours MTBF (25°C Full Load Operation)
- * International Safety Approvals & CE Mark
- * Class B Emissions
- * 3 Year Warranty



Input Specifications:

Input Range	Universal VAC (80-264 VAC) & 120-370 VDC
Input Frequency	47-63 Hz or DC
Inrush Current	25A @ 115VAC / 50A @ 230VAC max (cold start)
Input Current	0.85A @ 115 VAC Maximum
Input Reflected Ripple	FCC 68 part 15 Class B
Efficiency	88-89% Typical (depending on output model)
Input Protection	Single Fused (4 Amp / 250 V)
Hold-up Time	One Cycle Minimum @ 120 VAC and 80% load
Leakage Current	<750µA maximum @ 264 VAC
Harmonics	EN61000-3-2 Class D

Output Specifications:

Adjustment Range	Fixed
Minimum Load	None
Regulation	3% Maximum (Line, Load & Temp)
Ripple / Noise	± 1% pk-pk max (20MHz)
Transient Response	+/- 5% Deviation / < 1msec recovery
Set-Point Accuracy	±3%
Short Circuit Protection	Continuous
Over Load Protection	140-200%, automatic recovery
Over Voltage Protection	n/a

Emissions Standards

FCC Part 15J, Part 2	Within Class B Limits
EN55022 / CISPR22	Within Class B Limits

Electromagnetic Compatibility:

Electrostatic Discharge	EN61000-4-2, ±4KV Contact / ±8KV Air Discharge
Radiated Susceptibility	EN61000-4-3, 26-1000MHz, 10V/M, 80% AM
EFT / Bursts	EN61000-4-4, ± 2KV
Surges	EN61000-4-5, ±2KV Line-Earth, ±1KV Line-Line
Conducted Immunity	EN61000-4-6, 0.15 - 800MHz, 10V, 80% AM
Voltage Dips	EN61000-4-11, 95% Dip & 10ms, 30% Dip & 500ms
Voltage Interruptions	EN61000-4-11, 95% Reduction, 5s
Radiated Emissions	FCC 68 part 15 Class B
Conducted Emissions	FCC 68 part 15 Class B
Harmonic Current	EN61000-3-2 Class D
Fluctuations & Flicker	EN61000-3-3

Environmental Specifications:

Operating Temp	-20 ~50°C Full Load (De-Rate 2.5%/°C up to +70°C)
Storage Temp	-40 ~ +85°C
Cooling	5 cfm airflow required for full, or derate to 28W
Temp Co-Efficient	0.4% per °C
Humidity	5 to 95% RH Non-Condensing
Vibration	3grms / 3 Axes / 5-500Hz
Shock	30G Peak Acceleration
Reliability	>100k hours MTBF (Full Load and 25°C Operation)

International Safety Approvals

Standards	UL 60950-1 (2nd Edition) CB Report IEC 60950-1 CE Mark (LVD)
-----------	--

PowDec
Technologies, Inc.

PowDec Technologies (Taiwan) Inc.
No. 9, Alley 9, Lane 392, Fu Teh
1st Road Hsi Chih, Taipei Hsien, Taiwan, 22150
Tel: (02)2694-2760
Fax: (02)2694-2753
E-mail: powdec@ms3.hinet.net
http://www.powdec.com.tw


PowDec Technologies (USA) Inc.
7013 Realm Drive, Suite E
San Jose, CA 95119 U.S.A.
Tel: (408) 362-9388
E-mail: tedkang@powdec.com
http://www.powdec.com

Output Table:

Model Number	Vout	Iout	Efficiency
PTC40-12V	12V	3.33A	88%
PTC40-15V	15V	2.66A	88%
PTC40-24V	24V	1.66A	89%

Mechanical Specifications:

Construction: Open Frame




CN1: Molex 26-48-1035
Mates Molex 09-50-2030
(3-1) (2139 series)

Pin	Pin assignment:
1	Neutral
3	Line

CN2: Molex 26-48-1045
Mates with Molex 09-50-2040
(2139 series)

Pin	Pin assignment:
1	Vout
2	Vout
3	RTN
4	RTN



UNIT:mm ±1.0mm