


Flat indicator lights
 Flush-mounting
 Option: Waterproof IP64 / IP67 / IP68

Flach-Leuchten
 Oberflächenbündig montierbar
 Option: Wasserdicht IP64 / IP67 / IP68

Voyants lumineux plats
 Montage plat
 Option: Étanche IP64 / IP67 / IP68



183

184

188



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps		Accessories Zubehör Accessoires	Lens / Linse / Lentille		Light source Lichtquelle Source lum.	Resistor Widerstand Résistance			
	Protection Schutzart Protection	Surface Oberfläche Surface		with/mit/ avec Fresnel	Colour Farbe Couleurs		Code	V	mA	
183 LED terminals LED-Anschlüsse Fils des LED's	4	IP 64	B Brass, blackened Messing, geschwärzt Laiton, noircie	1 IP64 IP67 IP67 IP68 Torque Drehmoment Couple de rotation 4 Nm	A1	Amber Orange Orange	Y33U 4200 mcd Yellow Gelb Jaune Y30U 1200 mcd Y301 30 mcd B71G 6220 mcd B41G 1160 mcd G41N 17600 mcd G51N 10320 mcd G301 40 mcd R33U 4000 mcd R30U 1500 mcd R301 8 mcd	0	without ohne sans	
	7	IP 67	S Brass, nickel plated Messing, vernickelt Laiton, nickelée		B1	Blue Blau Bleue		A	5	20
	8	IP 68	9 Brass, olive drab * Messing, braunoliv * Laiton, olivebrun *		C1	Clear Klar Claire		B	12	20
184 Solder lugs Lötösen Contact à souder					G1	Green Grün Verte	D	24	20	
					R1	Red Rot Rouge	DB	24	15	
					W3	White Weiss Blanche	E	28	20	
188 Stranded wire Litze Fil multi-brins Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande						G1	EB	28	14	
						R1				
						W3				
						W37N 13350 mcd W36N 6900 mcd W32N 3745 mcd	White Weiss Blanche			
						RG36 common cathode only series 183 188 for 24V only 15mA for 28V only 14mA	Red-Green Rot-Grün Rouge-Verte			

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant / * except surface option 9 (none RoHS)

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

