



3D Step-file
available on request



Further specifications and options in section „E-G“ / Weitere Spezifikationen und Optionen in Kapitel „E-G“ / Autres spécifications et options au chapitre „E-G“

Type / Typ / Type	Body / Körper / Corps	Accessories Zubehör Accessoires		Cap / Farbkappe / Cabochon			Light source Lichtquelle Source lum.	Resistor Widerstand Résistance		
				Style Form Forme	with / mit avec Fresnel	Colour Farbe Couleurs		Code	V	mA
200 Stranded wire Litze Fil multi-brins Standard 100 mm Other lengths on request Andere Längen auf Anfrage Autres longueurs sur demande	1 Polycarbonate	1 Retainer Klemmscheibe Rondelle de serrage 1 Decorative washer Dekorations-scheibe Rondelle décorative nickel plated vernickelt nickelé 2 Decorative washer Dekorations-scheibe Rondelle décorative black schwarz noir 	0 Standard	A1 Amber Orange Orange 	Y54U 7000 mcd Y50U 3000 mcd Y501 80 mcd B91G 9000 mcd B21G 2120 mcd B61G 1160 mcd G81N 32500 mcd G71N 5620 mcd G501 80 mcd R54U 7000 mcd R50U 3000 mcd R521 80 mcd W55N 22000 mcd W50N 2320 mcd RG5F bipolar	Yellow Gelb Jaune Blue Blau Bleue Green Grün Verte Red Rot Rouge White Weiss Blanche Red-Green Rot-Grün Rouge-Verte 	0 without ohne sans A 5 20 B 12 20 D 24 20 E 28 20			

Operating Temperature -30° to +85°C (-40°C to +100°C on request) / Storage Temperature: -40° to +100°C

different LED's of the SLOAN range can be built in

RoHS compliant

Specifications are subject to change without notice - Änderungen die dem technischen Fortschritt dienen, sind vorbehalten - Réserve de modifications de toutes les données techniques

